

# Investigation of Parameter Uncertainties Inherent to the Geotechnical Design of Bank Revetments at Inland Waterways



Julia Sorgatz and Jan Kayser

**Abstract** This paper describes the effects of uncertainty inherent to the choice of hydraulic load and soil parameters on the geotechnical revetment design. As for the practitioner, the effect of uncertainties on the required armour layer thickness is studied. Uncertainties inherent to revetment design mainly result from the load and resistance parameters employed in the design. At present, design loads are obtained from empirical equations and worst-case ‘design vessel passages’. Characteristic soil parameters are defined on the basis of a limited number of field and laboratory tests. Thus, uncertainties arise with regard to the choice of characteristic values. In order to investigate the effects of parameter uncertainty on the revetment design, distributions and correlations of loads are assessed using vessel passages observed in the field. In ensuing uncertainty analyses it is found that at present available data does not allow approximating loads by means of probability functions, whereas for the soil parameters the results indicate that the minima of the soil parameters govern the design. However, it is also found that when considering more than one soil parameter as random variable, a less conservative design can be achieved as with the individual minima. As a conclusion, recommendations regarding parameter choice and design procedure are provided.

**Keywords** Uncertainty analysis · Revetment design · Slope stability under rapid drawdown · Characteristic values

## 1 Introduction

Bank revetments at German inland waterways are mainly secured by loose or grouted armour stones on a filter layer. Their design according to BAW Code of Practice: Principles for the Design of Bank and Bottom Protection for Inland Waterways (GBB) [1] encompasses a hydraulic and a geotechnical design, where the former defines the armour stone diameter necessary to withstand waves and currents and the

---

J. Sorgatz (✉) · J. Kayser  
Bundesanstalt Für Wasserbau (BAW), Karlsruhe, Germany  
e-mail: [julia.sorgatz@baw.de](mailto:julia.sorgatz@baw.de)

latter evaluates the embankment stability under a rapid water level drawdown. The presented study focuses on the geotechnical design.

The National Research Council [2, p. 2] states that “probabilistic methods, while not a substitute for traditional deterministic design methods, do offer a systematic and quantitative way of accounting for uncertainties encountered by geotechnical engineers, and they are most effective when used to organize and quantify these uncertainties for engineering designs and decisions.”

First investigations of uncertainties inherent to shore protection structures can be found in the Netherlands. Triggered by a severe storm event in 1953, van Danzig [3] presents a probabilistic approach for the geotechnical design of flood defence systems. Since then, numerous concepts for the design of sea defence structures, i. e. dikes, dunes and breakwaters, have been published, i. e. [4–9]. Approximately ten years ago, first studies of the hydraulic [10] and geotechnical stability [11, 12] of river and canal embankments were published, which focus on flood events and natural flow. So far, revetment stability under ship-induced loads has not been addressed.

The uncertainty inherent to the design of hydraulic structures is a result of aleatory and epistemic uncertainties. A third category of uncertainties are the so-called ‘unknown unknowns’ which refer to unidentified aleatory and epistemic uncertainties. This work primarily deals with aleatory uncertainty by introducing load and resistance parameters as random variables.

PIANC [13] states that the effects of ship or wind-induced water motion have a random character, however, to the knowledge of the authors, the uncertainty of ship-induced drawdowns and their effect on revetment design has not been investigated yet.

Sources of uncertainty inherent to resistance parameters are natural (inherent) variability, measurement error, transformation error and statistical uncertainty [14]. The natural variability is a result of the genesis of soil. Transformation uncertainty is “related to the accuracy of physical or statistical models” [14] and a result of empirical or other correlation models. For instance, the friction angle is usually determined by direct shear tests based on the relationship between measured shear stress failure and normal stress (Mohr-Coulomb failure criterion). Statistical uncertainty arises from the choice of probability function and its parameters. For the probability function of the effective friction angle  $\varphi'$ , Lacasse and Nadim [15], Wolff et al. [16], Lumb [17] and JCSS [18] suggest a Gaussian distribution, whereas Schultze [19] recommends a Lognormal distribution. The hydraulic conductivity  $k$  is commonly considered as lognormally distributed [20–22]. This paper focuses on statistical uncertainty. So far, the effects of different probability functions and parameters on revetment design have not been studied.

## 2 Reliability-Based Revetment Design: Theory and Methods

### 2.1 Principles of the Revetment Design

In simple terms, a vessel passage in a confined waterway cross-section, i. e. canal or river, leads to changed discharge conditions, which trigger a flow around the vessel and, thereby, cause a lowering of the water level next to the vessel, referred to as drawdown [1]. If the water level is lowered faster than the hydrostatic pore pressure in the soil can adapt to, excess pore pressure may develop (Fig. 1). This process is caused by a delayed pressure equalisation due to gas bubbles in the water at shallower depth [23, 24] and influenced by the compressibility of the water-gas-mixture [25, 26]. The excess pore pressure leads to reduced effective stress, which lowers the shear strength of the soil. This may result in local slope sliding or liquefaction [1].

Wave-induced drawdowns can be simplified by a uniformly decreasing water level with constant drawdown rate [23, 24]. The excess pore pressure attains a maximum at the end of the drawdown  $z_a$ , which allows to assess the acting forces as a steady-state problem. A depth-depending excess pore pressure  $\Delta p(z)$  may develop:

$$\Delta p(z) = \gamma_w z_a (1 - ae^{-bz}) \tag{1}$$

where  $\gamma_w$  is the unit weight of water and  $a = 1$  and  $b$  are pore pressure parameters;  $b$  describes the shape of  $\Delta p(z)$  as response to  $k$  and the ratio of design drawdown time  $t_a^* = 5$  s and drawdown time  $t_a$ , Eqs. (2) and (3), for a gas content of 5–15% in the pore fluid [25].

$$b^* = 0.166 \cdot k^{-0.327} \tag{2}$$




Fig. 1 Hydrostatic pore water pressure and excess pore pressure during rapid drawdown [1]

$$b = b^* \sqrt{\frac{t_a^*}{t_a}} \tag{3}$$

The excess pore pressure may cause driving forces to exceed resisting forces at the vertical slice of an infinite slope leading to local slope failure. The resisting forces are a function of buoyant unit weight of the soil  $\gamma'_B$ , slope inclination  $\beta$  and  $\phi'$ , the driving forces are governed by  $z_a$ . The difference of resisting and driving forces reaches a minimum at a critical depth  $d_{crit}$  as follows:

$$d_{crit} = \frac{1}{b} \ln \frac{\tan \phi' \gamma_w z_a b}{\cos \beta \gamma'_B (\tan \phi' - \tan \beta)} \text{ for } \phi' > \beta \tag{4}$$

If  $d_{crit} > 0$ , the equilibrium condition stated in Eq. (5) is used to determine the required unit weight of armour stones under buoyancy  $g'$ , which is the product of required armour layer thickness  $d_D$  and buoyant unit weight of armour stones  $\gamma'_D$ . Furthermore, Eq. (5) encompasses the filter layer thickness  $d_F$ , the buoyant unit weight of the filter layer  $\gamma'_F$ , the effective cohesion  $c'$  and the shear strength  $\tau$ , e.g. as a result of a toe support.

$$g' = \gamma'_D d_D = \frac{\Delta p \tan \phi' - c' - \tau}{\cos \beta \tan \phi' - \sin \beta} - (\gamma'_F d_F + \gamma'_B d_{crit}) \tag{5}$$


Waves and drawdown generate flow in permeable soils, which may lead to considerable vertical hydraulic gradients at bottom and bank and, thereby, liquefaction of near-surface soil layers. In the case of a toe support or a moderate slope inclination, the revetment dimensions determined in Eq. (5) may not satisfy the equilibrium of liquefaction given in Eq. (6) with the corresponding critical depth  $d_{critB}$  stated in Eq. (7).

$$g' = \gamma'_D d_D \geq \frac{\Delta p}{\cos \beta} - (\gamma'_F d_F + \gamma'_B d_{critB}) \tag{6}$$

$$d_{critB} = \frac{1}{b} \ln \left( \frac{\gamma_w z_a b}{\gamma'_B \cos \beta} \right) \tag{7}$$

A design according to GBB [1] fulfils the specifications, when the analyses demonstrate that the limiting equilibrium states (Eqs. 5, 6) are satisfied under the relevant combination of characteristic values. Characteristic values are “selected as a cautious estimate of the value affecting the occurrence of the limit state” [27]. Their selection is either based on expert knowledge or statistical methods. GBB [1] recommends a value at the lower end of the range of possible values for  $k$ ; for the choice of  $\phi'$  no recommendations are provided;  $z_a$  and  $t_a$  are derived from worst-case design vessel passages [28].

**Fig. 2** Parameter definition to compare the random analyses to deterministic benchmark solutions



## 2.2 Reliability Analyses and Parameter Combinations

The theory of reliability-based methods and their application in geotechnical engineering is well-known. Thus, for mathematical basics reference is made to literature [29, 30]. This paper directly presents the results of the uncertainty analyses, which are conducted with the Python package OpenTURNS [30]. A minimum of 10,000 Monte Carlo simulations is run to obtain a range of possible armour layer thicknesses. Subsequently, the 95% quantiles of the random output are computed to compare the probabilistic results to deterministic benchmark solutions.

The probability functions of the soil parameters are defined as follows: The mean value is constant, while the variability of the soil properties relative to the mean is governed by the coefficient of variation (cov). Different cov are investigated as indicated by the two probability density functions shown in Fig. 2. Since GBB [1] does not states particular bounds that represent characteristic values, a range of  $\phi'$  and  $k$  are considered for a deterministic benchmark solution. The lower bound of the benchmark solution is defined as the 5% quantile of the respective distribution. The upper bound of the deterministic benchmark solution is the mean of the respective distribution. For illustrative purposes, case studies with permeable sand (SW) and with silty sand (SU) are conducted. The variability of the soil is expressed via mean and cov. The soil parameters originate from the German design standard EAU [31].

As it will be shown in Sect. 3.1, currently available data does not support an uncertainty representation of drawdown parameters. The drawdown combinations used beyond Sect. 3.1 are thus based on literature and valid for a standardised rectangular trapezoidal waterway cross-section [28]. Combining loads and soil types, four case studies are investigated (see Table 1).

## 3 Results

### 3.1 Uncertainty of Loads

Two field campaigns conducted by the Bundesanstalt für Wasserbau (BAW) at Rhine river and Küsten Canal were used to investigate distributions and correlations of vessel-induced drawdowns. A campaign commonly lasted between one to two


**Table 1:** Combinations of loads and soil types with their physical properties based on literature [28, 31]

| Soil type |                     | Friction angle $\varphi'$ | $cov_{\varphi'}$ | Hydraulic conductivity k                | $cov_k$  | Unit weight $\gamma'_B$ | Time $t_a$ | Height $z_a$ |
|-----------|---------------------|---------------------------|------------------|---|----------|-------------------------|------------|--------------|
| —         |                     | °                         | —                | m/s                                     | —        | kN/m <sup>3</sup>       | s          | m            |
| SW1       | Sand, widely graded | 32.5–37.5                 | 0.01–0.10        | $1 \times 10^{-4}$ – $1 \times 10^{-5}$ | 0.1–1.00 | 11.5                    | 4.5        | 0.63         |
| SW2       | Sand, widely graded | 32.5–37.5                 | 0.01–0.10        | $1 \times 10^{-4}$ – $1 \times 10^{-5}$ | 0.1–1.00 | 11.5                    | 27.6       | 0.83         |
| SU1       | Silty sand          | 32.5–37.5                 | 0.01–0.10        | $1 \times 10^{-5}$ – $1 \times 10^{-6}$ | 0.1–1.00 | 9.5                     | 4.5        | 0.63         |
| SU2       | Silty sand          | 32.5–37.5                 | 0.01–0.10        | $1 \times 10^{-5}$ – $1 \times 10^{-6}$ | 0.1–1.00 | 9.5                     | 27.6       | 0.83         |

weeks. The measured values encompass dimensions and draught of the vessel, vessel velocity, passing distance and resulting water level fluctuations and flow velocities. Within the scope of this study only drawdowns are evaluated, which were recorded by absolute pressure probes at a minimum of two different heights.


It was found that based on the existing data drawdown parameters (1) are difficult to describe by generally valid probability functions; a Lognormal distribution tends to fit the data best (see Fig. 3), although not all datasets confirm this result. (2) With a Pearson coefficient  $\rho_p = 0.2$  there is no significant correlation between  $z_a$  and  $t_a$ .

Commonly, the armour layer thickness required to protect an embankment against slope sliding ranges between 0.60 and 0.80 m. The current analysis, however, results in armour layer thicknesses greater 1.00 m (see Fig. 4). It is assumed that, although, data analyses indicate a negligible correlation of  $z_a$  and  $t_a$ , random parameter combination and large uncertainty inherent to distribution fitting results in overly large revetment dimensions. Despite this fact, the observations raise the question whether



**Fig. 3** Examples of probability density functions of sternal drawdown height  $z_a$  and drawdown time  $t_a$ . Probability density functions of bow drawdowns are similar

**Fig. 4** Armour layer thickness obtained from the uncertainty analysis with random drawdown  $z_a$  and drawdown time  $t_a$ . It is obvious that the analysis results in significantly larger revetment dimensions than usual




current design drawdowns represent the most critical cases. In the future, long-term observations may assist in determining distributions and correlations of the drawdown parameters as well as critical drawdown combinations.


For now, deterministic loads as proposed in MAR [28], which are obtained from conservative equations in combination with worst case design scenarios, are used for further analyses. From the available load combinations, the most unfavourable are chosen (see Sect. 2.2, Table 1).

### 3.2 Effect of Parameter Uncertainty of Random Friction Angle or Hydraulic Conductivity

Figure 5 illustrates the effects of distribution uncertainty of  $\phi'$  on the armour layer thickness for two distribution types. It is observed that neither the permeable sand (SW) nor the silty sand (SU) requires a thicker armour layer as a result of the



**Fig. 5** Armour layer thickness as a function of  $cov_{\phi'}$  for permeable sand (left, SW) and silty sand (right, SU). The effective friction angle is approximated by a Lognormal (LOG) and a Gaussian (GAUSS) distribution. The hatched areas indicate the deterministic benchmark solutions obtained with the 5 and 50% quantiles of  $\phi'$ . The black graphs depict the 95% quantiles obtained from the uncertainty analysis with random  $\phi'$



**Fig. 6** Armour layer thickness as a function of  $cov_k$  for permeable sand (SW) and silty sand (SU). The hydraulic conductivity is approximated by a Lognormal distribution. The hatched areas indicate the deterministic benchmark solutions obtained with the 5 and 50% quantiles of  $k$ . The black graphs depict the 95% quantiles obtained from the uncertainty analysis with random  $k$ .

different distribution types. Eventually, with  $cov_{\phi'} > 0.1$ , the Gaussian distribution may lead to larger armour layer thicknesses. This observation agrees with Schneider and Schneider [32], who recommend the use of Lognormal distributions in particular for larger coefficients of variation ( $cov_{total} > 0.3$ ).

An increasing  $cov_{\phi'}$  leads to an increasing armour layer thickness. Depending on soil type and drawdown combination a maximum increase of 20 cm is observed for the investigated parameter range. In short, the uncertainty of  $cov_{\phi'}$  affects the uncertainty of the required armour layer thickness more than the choice of distribution. The design of less permeable soils is more strongly affected than the design of permeable soils.

The effects of the uncertainty of  $k$  on the required armour layer thickness are shown in Fig. 6. In contrast to  $\phi'$ , literature clearly states that a Lognormal distribution is the most suitable choice for  $k$ . Compared to the results with random  $\phi'$ , an uncertain  $k$  contributes more strongly to the uncertainty of the required armour layer thickness due to the larger variability of  $k$ . However, the required armour layer thickness does not rise linearly; the larger  $cov_k$  the smaller the increase of the armour layer thickness. Consequently, the variability of  $k$  affects the armour layer thickness less with increasing  $cov_k$ . In conclusion, the results confirm the recommendations of GBB [1] regarding the choice of the characteristic value of  $k$  as minimum observed in field or laboratory tests.

Finally, it is pointed out that for random  $\phi'$  and  $k$  the armour layer thickness in the SW cases is governed by the small  $t_a$  at moderate  $z_a$  (SW2), whereas the armour layer thickness in the SU cases is governed by the large  $t_a$  in combination with large  $z_a$  (SU1). This behaviour is explained by the time to reach a quasi-stationary state and, thus, the maximum excess pore pressure. In soils of smaller hydraulic conductivity it takes longer to reach a quasi-stationary state, while in permeable soils the quasi-stationary state is reached faster. In less permeable soil the maximum excess pore pressure is thus reached with large  $t_a$ , whereas small  $t_a$  do not allow the excess pore




pressure to fully build up. As a result, the SU cases require larger armour layer thicknesses with larger, but slower drawdowns, whereas the SW cases require more armour stones with smaller, but faster drawdowns. The observation emphasises the importance of investigating different drawdown combinations to identify the most critical combination.

### 3.3 Effect of Parameter Uncertainty of Random Friction Angle and Hydraulic Conductivity

The armour layer thickness obtained when considering combinations of random  $\phi'$  and  $k$  is shown in Fig. 7. Again, the choice of the probability function does not significantly affect the result. As the minima of  $\phi'$  and  $k$  govern the design, there is hardly any difference between the results obtained with Lognormal (LOG) and Gaussian (GAUSS)  $\phi'$ .

Compared to analyses with either random  $\phi'$  or  $k$ , the uncertainty inherent to the design increases when considering both,  $\phi'$  and  $k$ , as random. At the same time, it is observed that the random combination of  $\phi'$  and  $k$  results in smaller armour layer thicknesses than the deterministic 5% quantile result. Depending on the soil type, a maximum difference of approximately 15 cm is observed between deterministic benchmark solution and uncertainty analysis.

The analyses assume uncorrelated  $\phi'$  and  $k$ . However, in the case of the investigated parameters the correlation is slightly negative [32]. A zone that is characterised by small  $\phi'$  is more likely to be associated with high  $k$  and vice versa. Using the minima of  $\phi'$  and  $k$  as characteristic values may therefore result in a conservative design.



**Fig. 7.** Armour layer thickness as a function of  $cov_{\phi',k}$  for permeable sand (left, SW) and silty sand (right, SU). The effective friction angle is approximated by a Lognormal (LOG) and a Gaussian (GAUSS) distribution. The hatched areas indicate the deterministic benchmark solutions obtained with the 5% and 50% quantiles. The black graphs depict the 95% quantiles obtained from the uncertainty analysis with random  $\phi'$  and  $k$ .

## 4 Discussion and Conclusions

The analyses demonstrate that the majority of uncertainty inherent to the geotechnical revetment design results from the employed load combinations. At present available data does not allow approximating drawdowns by means of probability functions. Long-term observations may assist in determining adequate distributions and correlations. With an increased observation period it may also be conceivable to apply extreme value theory to determine characteristic values. At present, it is recommended that a design or assessment of the geotechnical design should explore a number of drawdown combinations, e.g. obtained from field observations or from MAR [28], to identify the most relevant drawdown combination.

The analysis with random soil parameters indicates that the choice of distribution type does not affect the armour layer thickness significantly. In contrast to that, the variance of soil parameters affects the required armour layer thickness significantly; if considered separately, the minima of  $\phi'$  and  $k$  govern the design.

Considering uncorrelated or negatively correlated soil parameters, the minima  $\phi'$  and  $k$  as characteristic values may result in an overly conservative design. The presented uncorrelated reliability analyses indicate that the armour layer thickness may be reduced by a maximum of 15 cm if considering both,  $\phi'$  and  $k$ , as random variables. For practical design purposes, this means that using reliability-based methods with random soil parameters and the combined 95%-exceedance value may allow for a more economic design than using the 5%-characteristic values of  $\phi'$  and  $k$ . Further investigations regarding the required target reliability and a corresponding semi-probabilistic design approach with partial factors are required.

To conclude with, it is important to note that the stability of a slope in rapid drawdown situations depends on the local excess pore pressure and shear strength. Therefore, it may not be sufficient to examine the statistical variability of the soil parameters. Future investigations that account for the spatial variability of soil, e.g. by means of random fields, may supplement current knowledge regarding the choice of characteristic soil parameters.

## References

1. GBB. (2010). *Grundlagen zur Bemessung von Böschungs- und Sohlsicherungen an Binnenwasserstraßen*. Bundesanstalt für Wasserbau: BAWMerkblatt.
2. National Research Council. (1995). *Probabilistic methods in Geotechnical Engineering*. Washington, D.C.: National Academies Press.
3. van Dantzig, D. (1956). Economic decision problems for flood prevention. *Econometrica*, 24(3), 276.
4. Bakker, K. J., & Vrijling, J. K. (1980). *Probabilistic design of sea defences*. Delft: Delft University of Technology.
5. Mol, A., Groeneveld, R. L., & Waanders, A. J. (1984). Safety and reliability of breakwaters. *Coastal Engineering Proceedings*, 1(19), 2451–2466.
6. Barends, F. B. J., & van Dijk, J. J. (1985). *Computer aided evaluation of the reliability of a breakwater design*. Zoetermeer: Final report CIAD.

7. van der Meer, J. W. (1988). *Rock Slopes and Gravel Beaches under Wave Attack*. Thesis. Delft Hydraulics Laboratory.
8. Vrijling, J. K. (2001). Probabilistic design of water defense systems in The Netherlands. *Reliability Engineering & System Safety*, 74(3), 337–344.
9. Kortenhaus, A. (2003). *Probabilistische Methoden für Nordseedeiche*. PhD thesis. Technische Universität Braunschweig.
10. Jafarnejad, M., Pfister, M., Brühwiler, E., & Schleiss, A. J. (2017). Probabilistic failure analysis of riprap as riverbank protection under flood uncertainties. *Stochastic Environmental Research and Risk Assessment*, 3(4), 1839–1851.
11. Möllmann, A. (2009). *Probabilistische Untersuchung von Hochwasserschutzdeichen mit analytischen Verfahren und der Finite-Elemente-Methode*. PhD thesis. Universität Stuttgart.
12. Weißmann, R. (2014). *Probabilistische Bewertung der Zuverlässigkeit von Flussdeichen unter hydraulischen und geotechnischen Gesichtspunkten*. PhD thesis. Karlsruher Institut für Technologie.
13. PIANC. (1987). Risk consideration when determining bank protection requirements. *Supplement to PIANC Bulletin*, 58, Permanent International Association of Navigation Congresses (PIANC).
14. ISO 2394 2015. *General principles on reliability for structures*.
15. Lacasse, S., & Nadim, F. (1996). Uncertainties in characterising soil properties (Plenary). In: C.D. Shackelford, P.P. Nelson, & M.J.S. Roth (Eds.), *Uncertainty in the geologic environment—From theory to practice. Proceedings of Uncertainty '96* (pp. 49–75). New York: American Society of Civil Engineers (ASCE).
16. Wolff, T.F., Demsky, E.C., Schauer, J., & Perry, E. (1996). Reliability assessment of dike and levee embankment. In: C. D. Shackelford, P. P. Nelson, & M. J. S. Roth (Eds.), *Uncertainty in the geologic environment—From theory to practice. Proceedings of Uncertainty '96* (pp. 636–650). New York: American Society of Civil Engineers (ASCE).
17. Lumb, P. (1966). The variability of natural soils. *Canadian Geotechnical Journal*, 3(2), 74–97.
18. JCSS. (2006). *Probabilistic model code. Section 3.7: Soil properties*. Joint Committee on Structural Safety.
19. Schultze, E. (1972). Frequency distributions and correlations of soil properties. In: Hong Kong University Press (Ed.), *Statistics and Probability in Civil Engineering*.
20. Carsel, R. F., & Parrish, R. S. (1988). Developing joint probability distributions of soil water retention characteristics. *Water Resources Research*, 24(5), 755–769.
21. Mallants, D., Mohanty, B. P., Vervoort, A., & Feyen, J. (1997). Spatial analysis of saturated hydraulic conductivity in a soil with macropores. *Soil Technology*, 10(2), 115–131.
22. de Rooij, G. H., Kasteel, R. T. A., Papritz, A., & Flühler, H. (2004). Joint distributions of the unsaturated soil hydraulic parameters and their effect on other variates. *Vadose Zone Journal*, 3(3), 947–955.
23. Köhler, H. J. (1993). The influence of hydraulic head and hydraulic gradient on the filtration process. In J. Brauns (Ed.), *Filters in geotechnical and hydraulic engineering* (pp. 225–240). Rotterdam: Balkema.
24. Köhler, H. J. (1997). Boden und Wasser—Druck und Strömung. *Mitteilungsblatt der Bundesanstalt für Wasserbau*, 76, 15–33.
25. Montenegro, H. (2016). *FuE-Abschlussbericht: Infiltrationsdynamik in Erdbauwerken*.
26. Ewers, J., Sorgatz, J., & Montenegro, H. (2017). Laborversuche und gekoppelte Berechnungen zur Untersuchung von Porenwasserüberdrücken infolge schneller Wasserstandsabsenkungen. In: Deutsche Gesellschaft für Geotechnik e.V. (DGGT) (Ed.), *Fachsektionstage Geotechnik der Deutschen Gesellschaft für Geotechnik*.
27. DIN EC7. (2015). Handbuch Eurocode 7—Geotechnische Bemessung. *Band 1, Deutsches Institut für Normung e. V. (DIN)*. Berlin: Beuth.
28. MAR. (2008). *Anwendung von Regelbauweisen für Böschungs- und Sohlensicherungen an Binnenwasserstraßen*. BAWMerkblatt, Bundesanstalt für Wasserbau.
29. Phoon, K.-K., & Ching, J. (2015). *Risk and reliability in geotechnical engineering*. Hoboken: Taylor and Francis.

30. Baudin, M., Dutfoy, A., Iooss, B., & Popelin, A.-L. (2015). *OpenTURNS. An industrial software for uncertainty quantification in simulation.*
31. EAU. (2012). *Empfehlungen des Arbeitsausschusses "Ufereinfassungen". Häfen und Wasserstraßen.* Deutsche Gesellschaft für Geotechnik e.V. (DGGT), Ernst, Berlin.
32. Vardon, P.J., Liu, K., & Hicks, M.A. (2016). Reduction of slope stability uncertainty based on hydraulic measurement via inverse analysis. *Georisk: Assessment and Management of Risk for Engineered Systems and Geohazards*, 10(3), 223–240.
33. Baecher, G. B., & Christian, J. T. (2003). *Reliability and statistics in geotechnical engineering.* Chichester: Wiley.
34. Schneider, H. R., & Schneider, M. A. (2013). Dealing with Uncertainties in EC7. In: P. Arnold, G.A. Fenton, M.A. Hicks, & T. Schweckendiek (Eds.), *Modern geotechnical design codes of practice* (pp. 87–101). Amsterdam: IOS Press.