

Novel Computerized Methods in System Biology – Flexible High-Content Image Analysis and Interpretation System for Cell Images

Petra Perner

Institute of Computer Vision and applied Computer Sciences, IBal
Arno-Nitzsche-Str. 43, 04277 Leipzig
pperner@ibai-institut.de
www.ibai-institut.de

Abstract. In the rapidly expanding fields of cellular and molecular biology, fluorescence illumination and observation is becoming one of the techniques of choice to study the localization and dynamics of proteins, organelles, and other cellular compartments, as well as a tracer of intracellular protein trafficking. The automatic analysis of these images and signals in medicine, biotechnology, and chemistry is a challenging and demanding field. Signal-producing procedures by microscopes, spectrometers and other sensors have found their way into wide fields of medicine, biotechnology, industrial and environmental analysis. With this arises the problem of the automatic mass analysis of signal information. Signal-interpreting systems which automatically generate the desired target statements from the signals are therefore of compelling necessity. The continuation of mass analysis on the basis of the classical procedures leads to investments of proportions that are not feasible. New procedures and system architectures are therefore required. We will present, based on our flexible image analysis and interpretation system *Cell_Interpret*, new intelligent and automatic image analysis and interpretation procedures. We will demonstrate it in the application of the HEp-2 cell pattern analysis.

Keywords: Image Analysis and Interpretation, High-Content Analysis of Images HCA, Automation and Standardization of Visual Inspection Tasks, Image-Mining, Systems for Knowledge Discovery and Interpretation, Microscopic Cell Image Analysis.

1 Introduction

In the rapidly expanding fields of cellular and molecular biology, fluorescence illumination and observation is becoming one of the techniques of choice to study the localization and dynamics of proteins, organelles, and other cellular compartments, as well as a tracer of intracellular protein trafficking.

Quantitative imaging of fluorescent proteins and patterns is accomplished with a variety of techniques, including wide-field, confocal and multiphoton microscopy, ultrafast low-light level digital cameras and multitracking laser control systems. These microscopic images can be of 2-dimensional or 3-dimensional nature, or even videos recording the life cycle of a cell.

Currently the interpretation of the resulting pattern in these digital images is usually done manually. However the huge amount of data created and the growing use of these techniques in industry for pharmacological aspects or diagnostic purposes in medicine require automatic image interpretation procedures. These image interpretation procedures should allow to interpret these images automatically, and also to detect automatically new knowledge to study the cellular and molecular processes.

The continuation of mass image analyses on the basis of the classical procedures leads to investments of proportions that are not feasible. New procedures based on image mining and case-based reasoning are therefore required.

We are developing methods that allow the automatic analysis of these images for the discovery of patterns, new knowledge and relations. The present work is applied to 2-dimensional microscopic fluorescent images, but will be continued with 3-d-image and video analysis. The aim of our work is to provide the system with image-analysis, feature-extraction and knowledge-discovery functions that are suited for mining a set of microscopic cell images for the automatic detection of image-interpretation knowledge and then applying this knowledge within the same system for automatic image interpretation of the HEP-2 cell images. At the end the system can work on-line in a pharmaceutical drug discovery process or in a medical laboratory process and automatically interpret the patterns on the cells in the image and calculate quantitative information about the cell pattern.

The developed processing functions should make the system flexible enough to deal with different kinds of cell-images and different image qualities and require a minimal number of interactions with the user for knowledge mining. The image-interpretation process is running fully automatically, based on the image-analysis and feature-extraction procedures developed for this kind of image analysis and the learned interpretation knowledge by the developed knowledge-mining procedures.

2 Challenges and Requirements to the Systems

Application-oriented systems that can only solve one specific task are very costly and it takes time to develop them. The success of automatic image-interpretation systems can only be guaranteed when the development effort is as low as possible and when they can be adapted quickly to different needs and tasks.

It is preferable that the automatic system not only calculates image features from the images but also maps the measurements to the desired information the user wants to obtain with his experiment. This views High-Content Image Analysis as a pattern recognition and image interpretation problem rather than as an image measurement problem where all possible image features are extracted from the images for further analysis. The pattern or the final information, such as e.g. “do the bacteria co-localize with the lysosomes”, is the central focus of the image analysis and the system should provide all functions that are necessary to achieve this result.

That requires developing systems that can run on a class of applications such as microscopic fluorescent images. Such systems should have functions that are able to:

- automatically detect single cells in the image regardless of the image quality with high accuracy, robustness, the ability for reproduction, and flexibility,

- automatically describe the properties of the cell nucleus and the cytoplasm by image features (numerical and symbolical),
- automatically interpret the images into cell patterns or other decisions (prediction),
- automatically detect new knowledge from image data and apply it to automatic interpretation.

The challenges are:

- New strategies are necessary that are able to adapt the system to changing environmental conditions during image capture, user needs and process requirements.
- Introduction of Case-Based-Reasoning (CBR) strategies and Data-Mining strategies [1] into image-interpretation systems on both the low-level and high-level to satisfy these requirements.

3 The Architecture

Our answer to this problem is a system architecture [2] named *Cell_Interpret* (see Figure 1) that is comprised of two main parts:

- the on-line part that is comprised of the image analysis and the image interpretation part.
- the off-line part that is comprised of the database and the data mining and knowledge discovery part.

These two units communicate over a database of image descriptions, which is created in the frame of the image-processing unit. This database is the basis for the image-mining unit.

The on-line part can automatically detect objects, extract image features from the objects and classify the recognized objects into the respective classes based on the prior stored decision rules. The interface between the off-line and the on-line part is the database where images and calculated image features are stored. The off-line part can mine the images for a prediction model or discover new groups of objects, features or relations. These similar groups can be used for learning the classification model or just for understanding the domain. In the later case the discovered information is displayed on the terminal of the system to the user. Once a new prediction model has been learnt the rules are inputted into the image interpretation part for further automatic interpretation after approval of the user.

Besides that there is an archiving and management part that controls the whole system and stores information for long-term archiving.

Images can be processed automatically or semi-automatically. In the first case, a set of images specified by the expert is automatically segmented into background and objects of interest and the feature extraction procedures installed in the image analysis system are used for each object to automatically calculate all features. All features are extracted regardless of their applicability for the specific application. This requires executing feature subset selection methods later on. For semi-automatic processing, an image from the image archive is selected by the expert and then is it displayed on the

monitor. To perform image processing an expert communicates with a computer. In this mode he has the option to calculate features based on the feature extraction procedures and/or record symbolic features based on his expert knowledge. This procedure ensures that also complicated image features, which are difficult to name, articulate or develop automatic feature extraction procedures, can also be taken into account and further evaluated by image mining. After the feature has been established by evaluating the acquired data base, the proper automatic feature extraction procedure can be developed and included into the system and made available for High-Content Analysis. The intelligence of the system will therefore incrementally improve.




Fig. 1. Architecture of Cell_Interpret

4 Case-Based Image Segmentation

Image segmentation is a process of dividing an image into a number of different regions such that each region is homogeneous with respect to a given property, but the union of any two adjacent regions is not.

Image thresholding is a well-known technique for image segmentation. Because of its wide applicability to many areas of digital image processing, a large number of thresholding methods have been proposed over the years (see, e.g., [3-5]). Image thresholding has low computational complexity, which makes it an attractive method, but does not take into account spatial information and is mostly suitable for images where the gray-levels constitute well defined peaks, separated by not too broad and flat valleys.

Another common approach to image segmentation is based on feature space clustering, which has sometimes been regarded as the multidimensional extension of the concept of thresholding. Clustering schemes using different kinds of features (multi-spectral information, mean/variation of gray-level, texture, color) have been suggested (see, e.g., [6-8]). This approach can be successfully used if each perceived region of the image constitutes an individual cluster in the feature space. This requires a careful selection of the proper features, which depends on image domain.

Segmentation can also be accomplished by using region-based methods, or edge-detection-based methods, or methods based on a combination of those two approaches (see, e.g., [9-11]). Region-based methods imply the selection of suitable seeds from which to perform a growing process. In general, region merging and region splitting are accomplished to obtain a meaningful number of homogeneous regions. Seed selection and homogeneity criterion play a critical role for the quality of the obtained results. Edge-detection-based methods follow the way in which human observers perceive objects, as they take into account the difference in contrast between adjacent regions. Edge detection does not work well if the image is not well contrasted, or in the presence of ill-defined or too many edges.

Watershed-based segmentation (see, e.g., [12]) exploits both region-based and edge-detection-based methods. The basic idea of watershed-based segmentation is to identify in the gray-level image a suitable set of *seeds* from which to perform a growing process. If the main feature taken into account is gray-level distribution, the seeds are mostly detected as the sets of pixels with locally minimal gray-level (called *regional minima*). The growing process groups each seed with all pixels that are closer to that seed than to any other seed, provided that a certain homogeneity in gray-level is satisfied. Thus, watershed-based segmentation limits the drawbacks of region-based and edge-detection-based methods.

To overcome the drawbacks of the algorithms mentioned above, learning methods are applied to image segmentation. These learning methods are applied to learn the mapping between image features and semantically meaningful parts, to learn the parameters of the segmentation algorithm or to learn the mapping between rank performance of the segmentation algorithm and the image features.

There are statistical learning methods, machine learning methods, neural-net-based learning methods, and learning methods using a combination of different techniques. The main drawbacks of these methods are: 1) the need of a sufficiently large training set, and 2) the need of training again the whole model, when new data come in. Therefore, it seems to be useful to use Case-based Reasoning (CBR) for a flexible image segmentation system, since CBR can be used as a reasoning approach as well as an incremental knowledge-acquisition approach.

We propose a novel image-segmentation scheme based on case-based reasoning. We use CBR for meta-learning of the segmentation parameters (see Section 4.1) and for case-based object recognition (see Section 4.2).

4.1 CBR Meta Learning for Image Segmentation

The case-based reasoning unit for meta learning of image segmentation parameters [13] consists of a case base in which formerly processed cases are stored. A case is comprised of image information, non-image information (e.g. image-acquisition

parameters, object characteristics and so on), and image-segmentation parameters. The task is now to find the best segmentation for the current image by looking up the case base for similar cases. Similarity determination is done based on non-image information and image information. The evaluation unit will take the case with the highest similarity score for further processing. In case there are two or more cases with the same similarity score, the case appearing first will be taken. After the closest case has been chosen, the image-segmentation parameters associated with the selected case will be given to the image-segmentation unit and the current image will be segmented (see Figure 2). It is assumed that images having similar image characteristics will show similar good segmentation results when the same segmentation parameters are applied to these images. The image segmentation algorithm is in our case a histogram-based image-segmentation algorithm [13] and a watershed-based image-segmentation algorithm [14].




Fig. 2. CBR Image Segmentation Unit

The result of the segmentation process can be observed by the user or an automatic evaluation procedure. When the evaluation is done by the user, he compares the original image with the labeled image on display. If he detects deviations of the marked areas in the segmented image from the object area in the original image, which should be labeled, then he will evaluate the result as incorrect and case-base management will start. This will also be done if no similar case is available in the case-base. The proposed method is close to the critique-modify framework described by Grimnes et al. [15].

The evaluation procedure can also be done automatically. However, the drawback is that there is no general procedure available. It can only be done in a domain-dependent fashion.

Once the chosen evaluation procedure observes a bad result, the respective case is tagged as bad case. The tag describes the critique in more detail.

In an off-line phase, the best segmentation parameters for the image are determined by an optimization procedure and the attributes/features, which are necessary for

similarity determination, are calculated from the image. Both, the segmentation parameters and the attributes calculated from the image, are stored into the case-base as a new case. In addition to that the non-image information is extracted from the file header and stored together with the other information in the case-base. During storage, case generalization will be done to ensure that the case base will not become too large.

4.2 Case-Based Object Recognition

We propose our case-based object recognition method to recognize objects by their shape. In contrast to traditional object recognition methods [16] our method is comprised of a case mining part and the object recognition part [17]. The case mining part can learn the desired contour of the object and the number of contours necessary for recognizing a particular class of objects. The learnt contours make up the case base and are the basis for the case-based object-recognition method.

The objects in the image may be occluded, touching, or overlapping. It can also happen that only part of the object appears in the image.

A case-based object-recognition method uses cases that generalize the original objects and matches them against the objects in the image, see Fig. 3. During this procedure a score is calculated that describes the quality of the fit between the object and the case. The case can be an object model which describes the inner appearance of the object as well as its contour. In our case the appearance of the whole object can be very diverse. The shape seems to be the feature that generalizes the objects. Therefore, we decided to use contour models. We do not use the gray values of the model, but instead use the object's edges. For the score of the match between the contour of the object and the case we use a similarity measure based on the scalar product. It measures the average angle between the vectors of the template and the object.




Fig. 3. Principle of case-based object-recognition architecture

The acquisition of the case is done semi-automatically. Prototypical images are shown to an expert. The expert manually traces the contour of the object with the help of the cursor of the computer. Afterwards the number of contour points is reduced for data-reduction purposes by interpolating the marked contour by a first-order polynomial. The marked object shapes are then aligned by the Procrustes Algorithm [18]. From the sample points the direction vector is calculated. From a set of shapes general groups of shapes are learnt by conceptual clustering which is a hierarchical incremental clustering method [19]. The prototype of each cluster is calculated by estimating the mean shape [19] of the set of shapes in the cluster and is taken as a case model.

5 Automatic and Symbolic Feature Extraction

The system can now, based on the feature-extraction procedure installed in the system, calculate image features for the labeled objects. These features are composed of statistical gray-level features, the object contour, square, diameter, shape, [20] and a novel texture feature based on random sets [21] that is flexible enough to describe different textures of cells. The system evaluates or calculates image features and stores their values in a database of image features. Each entry in the database presents features of the object of interest. These features can be numerical (calculated on the image) and symbolical (determined by the expert as a result of image reading by the expert). In the latter case the expert evaluates object features according to the attribute list, which has to be specified in advance for object description, or is based on a visual ontology available for visual content description. Then the user feeds these values into the database. When the expert has evaluated a sufficient number of images, the resulting database can be used for the image-mining process.

6 Image Mining and Knowledge Discovery

The image mining part should allow extracting knowledge or making observations from different perspectives. Therefore, we have included methods for predictions and methods for knowledge discovery [1]. Knowledge discovery methods allow us to summarize data into groups and patterns or observe relations among groups. Usually they are prior to prediction. We prefer conceptual clustering [1] for this task since the discovery process is incremental and therefore fits perfectly to case-based reasoning and decision tree induction as prediction methods.

6.1 Decision Tree Induction

Decision tree induction allows one to learn from a set of data samples a set of rules and basic features necessary for decision-making in a specified diagnostic task, see Figure 4. The induction process does not only act as a knowledge discovery process, it also works as a feature selector, discovering a subset of features that is the most relevant to the problem solution.

Decision trees partition decision space recursively into sub-regions based on the sample set.

In this way the decision trees recursively break down the complexity of the decision space. The outcome has a format which naturally presents a cognitive strategy that can be used for the human decision-making process. The rules contained in the tree can be understood by human. Therefore a decision tree is a representation form that has explanation capability.

For any tree all paths lead to a terminal node, corresponding to a decision rule that is a conjunction (AND) of various tests. If there are multiple paths for a given class, then the paths represent disjunctions (ORs).

The developed tool allows choosing different kinds of methods for feature selection, feature discretization, pruning of the decision tree and evaluation of the error rate. It provides an entropy-based measure, a gini-index, gain-ratio and chi square method for feature selection [1].

The following methods for feature discretization are provided: cut-point strategy, chi-merge discretization, minimum description length, principal based discretization method and lvq-based method [1]. These methods allow one to make discretization of the feature values into two and more intervals during the process of decision-tree building. Depending on the chosen method for attribute discretization, the result will be a binary or n-ary tree. The later will lead to more accurate and compact trees.

The tool allows one to chose between cost-complexity pruning, error-reduction-based methods and pruning by confidence-interval prediction. The tool also provides functions for outlier detections.

To evaluate the obtained error rate one can choose test-and-train and n-fold cross validation. Missed values can be handled by different strategies [1].

The user selects the preferred method for each step of the decision tree induction process. After that the induction experiment can start on the acquired database. A resulting decision tree will be displayed to the user. He/she can evaluate the tree by checking the features used in each node of the tree and comparing them with his/her domain knowledge.




Fig. 4. Basic Principle of Decision Tree Induction

Once the diagnosis knowledge has been learnt, the rules are provided either in txt-format or XML format for further use in the image interpretation part or the expert can use the diagnosis component of the tool for interactive work. It has a user-friendly interface and is set up in such a way that non-computer specialists can handle it very easily.

6.2 Case-Based Reasoning for Image Interpretation

It is difficult to apply decision trees in domains where generalized knowledge is lacking. But often there is a need for a prediction system, even though there is not enough generalized knowledge. Such a system should a) solve problems using the already stored knowledge and b) capture new knowledge, making it immediately available to solve the next problem. To accomplish these tasks case-based reasoning is useful. Case-based reasoning explicitly uses past cases from the domain expert's successful or failing experience.

Therefore, case-based reasoning can be seen as a method for problem-solving as well as a method to capture new experience in an incremental fashion and make it immediately available for problem-solving. It can be seen as a learning and knowledge-discovery approach, since it can capture from new experience some general knowledge such as case classes, prototypes and some higher-level concepts. We find these methods especially applicable for inspection and diagnosis tasks. In the case of these applications people store prototypical images into a digital image catalogue rather than a large set of different images [22].

We have developed a unit for *Cell_Interpret* that can perform similarity determination between cases, as well as prototype selection [23] and feature weighting [24]. We call $x_n \in \{x_1, x_2, \dots, x_n\}$ a nearest-neighbor to x if $\min d(x_i, x) = d(x_n, x)$, where $i = 1, 2, \dots, n$. The instance x is classified into category C_n , if x_n is the nearest neighbor to x and x_n belongs to class C_n .

In the case of the k -nearest neighbor we require k -samples of the same class to fulfill the decision rule. As a distance measure we use the Euclidean distance. Prototype Selection from a set of samples is done by Chang's Algorithm [23]. Suppose a training set T is given as $T = \{t^1, \dots, t^m\}$. The idea of the algorithm is as follows: We start with every point in T as a prototype. We then successively merge any two closest prototypes p^1 and p^2 of the same class by a new prototype p , if the merging will not downgrade the classification of its patterns in T . The new prototype p may simply be the average vector of p^1 and p^2 . We continue the merging process until the number of incorrect classifications of the patterns in T starts to increase.

The wrapper approach is used for selecting a feature subset from the whole set of features. This approach conducts a search for a good feature subset by using the k -NN classifier itself as an evaluation function. The 1-fold cross-validation method is used for estimating the classification accuracy and the best-first search strategy is used for the search over the state space of possible feature combination. The algorithm terminates if we have not found an improved accuracy over the last k search states. The feature combination that gave the best classification accuracy is the remaining

feature subset. After we have found the best feature subset for our problem, we try to further improve our classifier by applying a feature-weighting technique.

The weights of each feature w_i are changed by a constant value δ : $w_i := w_i \pm \delta$. If the new weight causes an improvement of the classification accuracy, the weight will be updated accordingly; if not, the weight will remain as it is. After the last weight has been tested the constant δ will be divided into half and the procedure repeats. The procedure terminates if the difference between the classification accuracy of two iterations is less than a predefined threshold.

6.3 Conceptual Clustering

The intention of clustering as another image mining function is to find groups of similar cases among the data according to the observation. This can be done based on one feature or a feature combination. The resulting groups give an idea how data fit together and how they can be classified into interesting categories.

Classical clustering methods only create clusters but do not explain why a cluster has been established. Conceptual clustering methods build clusters and explain why a set of objects confirm a cluster. Thus, conceptual clustering is a type of learning by observation and it is a way of summarizing data in an understandable manner [1]. In contrast to hierarchical clustering methods, conceptual clustering methods build the classification hierarchy not only based on merging two groups. The algorithmic properties are flexible enough to dynamically fit the hierarchy to the data. This allows incremental incorporation of new instances into the existing hierarchy and updating this hierarchy according to the new instance.

A concept hierarchy is a directed graph in which the root node represents the set of all input instances and the terminal nodes represent individual instances. Internal nodes stand for sets of instances attached to the nodes and represent a super-concept. The super-concept can be represented by a generalized representation of this set of instances such as the prototype, the mediod or a user selected instance. Therefore a concept C , called a class, in the concept hierarchy is represented by an abstract concept description and a list of pointers to each child concept $M(C) = \{C_1, C_2, \dots, C_i, \dots, C_n\}$, where C_i is the child concept, called subclass of concept C .

Our conceptual clustering algorithm presented here is based on similarities, because we do not consider logical but numerical concepts [19].

The output of our algorithm for applying eight exemplary shape cases of fungal strain *Ulocladium Botrytis* is shown in Figure 5. On top level the root node is shown which comprises the set of all input cases. Successively the tree is partitioned into nodes until each input case forms its own cluster.

The main advantage of our conceptual clustering algorithm is that it brings along a concept description. Thus, in comparison to agglomerative clustering methods, it is easy to understand why a set of cases forms a cluster. During the clustering process the representative case, and also the variances and maximum distances in relation to this representative case, are calculated, since they are part of the concept description. The algorithm is of incremental fashion, because it is possible to incorporate new cases into the existing learnt hierarchy.




Fig. 5. Output of the Conceptual Clustering Algorithm for 2-D Shapes obtained from Fungal Spores

7 Results

The kinds of cells that are considered in this application are HEP-2 cells, which are used for the identification of antinuclear autoantibodies (ANA). ANA testing for the assessment of systemic and organ-specific autoimmune diseases has increased progressively since immunofluorescence techniques were first used to demonstrate antinuclear antibodies in 1957. HEP-2 cells allow for recognition of over 30 different nuclear and cytoplasmic patterns, which are given by upwards of 100 different autoantibodies.

The identification of the patterns has up to now been done manually by a human inspecting the slides with the help of a microscope. The lacking automation of this technique has resulted in the development of alternative techniques based on chemical reactions, which do not have the discrimination power of the ANA testing. An automatic system would pave the way for a wider use of ANA testing.

Prototypical images of HEP-2 cell patterns for six different classes are shown in Figure 6. The images were taken by an image-acquisition unit consisting of a microscope AXIOSKOP from Carl Zeiss Jena, coupled with a video camera.

In a knowledge-acquisition process [25] with a human operator, using an interview technique and a repertory grid method, we acquired the knowledge of this operator, while classifying the different cell types. Some of this knowledge is shown in table 1. The symbolic terms show that a mixture of different image information is necessary for classification. The operator uses the intensity as well as some texture information. In addition, the appearances of the cell parts within the cells are of importance, like “dark nucleoi”, which also requires spatial information.




Fig. 6. Prototypical Images of Six Classes

Each image is processed by the image-analysis procedure described in the previous section. The color image is transformed into a gray-level image. The image is normalized to the mean and standard gray level calculated from all images to avoid invariance caused by the inter-slice staining variations. Automatic thresholding has been performed by the algorithm described in Section 4.1. For the objects in each slice, features based on the texture descriptor described in Section 5 are calculated for classification [26]. The first one is a simple Boolean feature which expresses the occurrence or non-occurrence of objects in the slice image. Then the number of objects in the slice image is calculated. From the objects, the area, a shape factor, and the length of the contour are calculated. The mean value for each feature is calculated over all the objects in the slice image. This is done in order to reduce the dimension of the feature vector. Since the quantization of the gray level was done in equal steps and without considering the real nature, we also calculated for each class the mean value of the gray level and the variance of the gray level. A total of 192 features were calculated that make up a very intelligent structure and texture descriptor for cells [26]. The data base created from 7-10 images per class which made up 200 cells per class is given to our decision tree unit. This unit learns the classification knowledge based on decision tree induction. Finally, the system was evaluated based on cross validation. The final result is shown in table 2. The overall classification accuracy is 92.73%. The class specific classification accuracy [1] is shown for each class in table 2 on the right side of the table and the classification quality for each class in the bottom line of the table. In most of the classes we achieved good classification accuracy. There are only few classes where the classification accuracy is not as good as the other ones. It is interesting to note that in case of class_5 four cases got misclassified as class_14 “U1-RNP” but when checking with the expert it tended out that the classifier put these samples in the right class. The case was that the expert mislabeled the cases as class_5

Table 1. Some knowledge about the class description given by a human operator

Class	ClassName	Description
Homogeneous nuclei fluorescence	Class_1	Smooth and uniform fluorescence of the nuclei. Nuclei appear sometimes dark. The chromosome fluorescence is from weak to very intense
Fine speckled nuclei fluorescence	Class_2	Dense fine speckled fluorescence
...
Nuclei fluorescence	Class_9	Nuclei are weakly homogenous or fine-grained and can hardly be discerned from the background

while the automatic system recognized that these samples belong not to class_5 but to class_14. This example shows nicely that an automatic system can lead to standardization of cell image classification. It provides objective results, it works constantly without getting tired and the results are reproducible.

The computation time of an image for the Hep-2 application is 10 seconds by an image size of 1600x1200. This computation time is fast enough for the considered application and for most other applications. Users who like to have a faster computation time can easily speed up the computation time by parallelization. Parallelization can be done in the simplest case by using more than one computer. In the hardest case, the whole algorithm can be programmed in parallel fashion.

The methods developed within the framework *Cell_Interpreter* have been applied to many different applications of microscopic cell images including Hep-2 cell, HeLa-cells and Malaria diagnosis. They showed to be flexible enough for different kind of cell images diagnosis tasks and they efficiently enabled the mining of the relevant knowledge for the development of an automatic image interpretation system.

The Hep-PAD version developed based on *Cell_Interpreter* has been licensed to qualified industries and is meanwhile a commercial application in usage at different medical laboratories.

We are currently further developing the framework of *Cell_Interpreter* to video microscopy and developing more feature extraction and image mining procedure that can further support the image mining process.

8 Expert Opinion

Recent developments are highly application oriented. Often the system works only in a semi-automatic modus [27][28] that puts a lot of work to the user using the system. Standard image processing methods are applied to specific tasks combined with a lot of heuristics [31] to make the methods more or less automatically work on the specific images.

Table 2. Results for Hep-2 Pattern Analysis

Example: Result LDS6 and DMA																	
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Sum	Class Specific Quality
	AntiCent	Actin	AMA Who	Centromer	CoaresSp	Homogen	Job-1	Nucleolar	PMSQL	SCL70	Speckled	SS-A	SS-B	UI-FNP	Vimentin		CSQ
AntiCent	6															6	100,00%
Actin		7														7	100,00%
AMA Who			7													7	100,00%
Centromer				7												7	100,00%
CoaresSp					5						2					7	71,43%
Homogen						8										8	100,00%
Job-1							6									6	100,00%
Nucleolar								7								7	100,00%
PMSQL									7							7	100,00%
SCL70										8						8	100,00%
Speckled											6					6	100,00%
SS-A							1					7				8	87,50%
SS-B													7			7	100,00%
UI-FNP														7		12	58,33%
Vimentin															7	7	100,00%
Sum	6	7	7	7	9	8	7	7	7	8	9	7	7	7	7	110	
Cl. Qual.	100,00%	100,00%	100,00%	100,00%	55,56%	100,00%	85,71%	100,00%	100,00%	100,00%	66,67%	100,00%	100,00%	100,00%	100,00%		94,48%

Classification Quality

Total Number of samples	110
Correct classified samples	102
Correctness	92,73%
Error rate	7,27%

110
106
96,36%
3,64%

One such method is the Watershed-Transformation (WT) for image segmentation [27-31]. We have developed a flexible and automatic Case-Based Watershed Transformation method where the WT can be adapted to the image characteristics of the image under consideration.

Standard texture feature extraction procedures are used as well [32] but the random set approach as described here does have the flexibility to describe the different particles appearing in a cell and their randomness.

Application-oriented systems that can only solve one specific task are very costly and it takes time to develop them. The success of automatic image-interpretation systems can only be guaranteed when the development effort is as low as possible and when they can be adapted quickly to different needs and tasks. The proposed architecture of *Cell_Interpret* will help to overcome this problem.

There are commercial High-Content Analysis developments where data mining capabilities are included in the system. However, a better understanding of when and how to apply these methods and how to interpret the results are necessary for the user. Therefore we are constantly working on a methodology of data mining that is presented in our data mining tutorial (www.data-mining-tutorial.de) and copied in our data mining tools included in *Cell_Interpret*.

Another interesting observation in high-content analysis is that of images are created by using different staining to make specific cell details/objects visible [33][34]. It is obvious that in the resulting images the specific object details/parts are most visible and the analysis of these images can be simply made. However for a computer vision expert arises the question if this approach is really necessary in all case studies or would it be better to consider the whole task as a pattern recognition problem as has been done in the HEp-2 cell application and study the different patterns that appear when treating the cells in different ways. This statement might be a bit provocative and we have to admit that we do not know all applications in HCA but we would be happy to further discuss this with experts from the domain.

We also think that a better categorization of the different image analysis tasks is necessary to ensure a standardization of the image analysis procedures in HCA. A first study in that direction has been given in [35] [36]. Biologists, computer scientists and all other people involved in this field need to further discuss this and find a common basis of understanding.

The case-based reasoning approach in our system architecture *Cell_Interpret* we are recently been further developing for cell-tracking and 3D image analysis.

9 Conclusion

In this paper we have presented our architecture, *Cell_Interpret*, for High-Content Image Analysis and the methods used for the different tasks such as image segmentation, feature extraction, image mining and classification and interpretation. Most of the methods are based on case-based reasoning. CBR solves problems using already stored knowledge, and captures new knowledge, making it immediately available for solving the next problem. Therefore, case-based reasoning can be seen

as a method for problem solving, and also as a method to capture new experience and make it immediately available for problem solving. It can be seen as a learning and knowledge-discovery approach, since it can capture from new experience some general knowledge, such as case classes, prototypes and some higher-level concepts.

The idea of case-based reasoning originally came from the cognitive science community which discovered that people are reasoning on formerly successfully solved cases rather than on general rules. Our interest is to build intelligent flexible and robust data-interpreting systems [37][38][39] that are inspired by the human case-based reasoning process and by doing so to model the human reasoning process when interpreting the cell images.

References

1. Perner, P.: *Data Mining on Multimedia Data*. LNCS, vol. 2558. Springer, Heidelberg (2002)
2. Perner, P.: Utility model, computer system for the automatic data analysis, classification, interpretation and data mining of cells, cell structures, microorganism, biotic particle, parts and products in digital images, DE 20206003294 U1
3. Wang, L., Bai, J.: Threshold selection by clustering gray levels of boundary. *Pattern Recognition Letters* 24(12), 1983–1999 (2003)
4. Demirkaya, O., Asyali, M.H.: Determination of image bimodality thresholds for different intensity distributions. *Signal Processing: Image Communication* 19(6), 507–516 (2004)
5. Patricio, M.A., Maravall, D.: A novel generalization of the gray-scale histogram and its application to the automated visual measurement and inspection of wooden Pallets. *Image and Vision Computing*, 2006 25(6), 805–816 (2007)
6. Pauwels, E.J., Frederix, G.: Finding Salient Regions in Images: Nonparametric Clustering for Image Segmentation and Grouping. *Computer Vision and Image Understanding* 75 (1-2), 73–85 (1999)
7. Cutrona, J., Bonnet, N., Herbin, M., Hofer, F.: Advances in the segmentation of multi-component microanalytical images. *Ultramicroscopy* 103(2), 141–152 (2005)
8. Filin, S., Pfeifer, N.: Segmentation of airborne laser scanning data using a slope adaptive neighborhood. *ISPRS Journal of Photogrammetry and Remote Sensing* 60(2), 71–80 (2006)
9. Kermad, C.D., Chehdi, K.: Automatic image segmentation system through iterative edge-region co-operation. *Image and Vision Computing* 20(8), 541–555 (2002)
10. Muñoz, X., Freixenet, J., Cufí, X., Martí, J.: Strategies for image segmentation combining region and boundary information. *Pattern Recognition Letters* 24(1-3), 375–392 (2003)
11. Voss, T.C., Demarco, I.A., Day, R.N.: Quantitative Imaging of Protein Interactions in the cell nucleus. *Biotechniques* 38(3), 413–424 (2005)
12. Beucher, S., Meyer, F.: The morphological approach of segmentation: the watershed transformation. In: Dougherty, E. (ed.) *Mathematical Morphology in Image Processing*, pp. 433–481. Marcel Dekker, New York (1993)
13. Perner, P.: An architecture for a CBR image segmentation system. *Journal of Engineering Application in Artificial Intelligence* 12(6), 749–759 (1999)
14. Frucci, M., Perner, P., Sanniti di Baja, G.: Case-based Reasoning for Image Segmentation by Watershed Transformation. In: Perner, P. (ed.) *Case-Based Reasoning on Signals and Images*. Springer, Heidelberg (2007)

15. Grimnes, M., Aamodt, A.: A two layer case-based reasoning architecture for medical image understanding. In: Smith, I., Faltings, B.V. (eds.) EWCBR 1996. LNCS, vol. 1168, pp. 164–178. Springer, Heidelberg (1996)
16. Knowles, D.W., Sudar, D., Bator-Kelly, C., Bissell, M.J., Lelievre, S.A.: Automated local bright feature image analysis of nuclear protein distribution identifies changes in tissue phenotype. *PNAS* 103(12), 445–4445 (2006)
17. Perner, P., Perner, H., Jänichen, S.: Recognition of Airborne Fungi Spores in Digital Microscopic Images. *Journal Artificial Intelligence in Medicine AIM, Special Issue on CBR* 36(2), 137–157 (2006)
18. Dryden, I.L., Mardia, K.V.: *Statistical Shape Analysis*. John Wiley & Sons, Chichester (1998)
19. Jaenichen, S., Perner, P.: Conceptual Clustering and Case Generalization of two-dimensional Forms. *Computational Intelligence* 22(3/4), 178–193 (2006)
20. Zamperoni, P.: Feature Extraction. In: Maitre, H., Zinn-Justin, J. (eds.) *Progress in Picture Processing*, pp. 121–184. Elsevier Science, Amsterdam (1996)
21. Perner, P., Perner, H., Müller, B.: Mining Knowledge for Hep-2 Cell Image Classification. *Journal Artificial Intelligence in Medicine* 26, 161–173 (2002)
22. Perner, P.: *Prototype-Based Classification Applied Intelligence* (to appear) (online available)
23. Chang, C.-L.: Finding Prototypes for Nearest Neighbor Classifiers. *IEEE Trans. on Computers* C-23(11), 1179–1184 (1974)
24. Wettschereck, D., Aha, D.W.: Weighting Features. In: Aamodt, A., Veloso, M.M. (eds.) *ICCBR 1995*. LNCS, vol. 1010, pp. 347–358. Springer, Heidelberg (1995)
25. Perner, P.: Image Mining: Issues, framework, a generic tool and its application to medical-image diagnosis. *Journal Engineering Applications of Artificial Intelligence* 15(2), 193–203
26. Perner, P., Perner, H., Müller, B.: Texture Classification based on Random Sets and its Application to Hep-2 Cells. In: Kasturi, R., Laurendeau, D., Suen, C. (eds.) *ICPR 2002*, vol. II, pp. 406–411. IEEE Computer Society, Los Alamitos (2002)
27. Gokay, K.E., Wilson, J.M.: Targeting of an Apical Endosomal Protein to Endosomes in Madin–Darby Canine Kidney Cells Requires Two Sorting Motifs. *Traffic* 1, 354–365 (2000)
28. Beil, M., Dürschmied, D., Paschke, St., Schreiner, B., Nolte, U., Bruel, A., Irinopoulou, T.: Spatial Distribution Patterns of Interphase Centromeres During Retinoic Acid-Induced Differentiation of Promyelocytic Leukemia Cells. *Cytometry* 47, 217–225 (2002)
29. Velliste, M., Murphy, R.F.: Automated determination of protein subcellular locations from 3D fluorescence microscope images. In: *Proc. Biomedical Imaging 2002*, pp. 867–870. IEEE Press, Los Alamitos (2002)
30. Irinopoulou, T., Vassy, J., Beil, M., Nicol, P.: Three-Dimensional DNA Image Cytometry by Confocal Scanning Laser Microscopy in Thick Tissue Blocks of Prostatic Lesions. *Cytometry* 27, 99–105 (1997)
31. Swedlow, J.R., Goldberg, I., Brauner, E., Sorger, P.K.: Informatics and Quantitative Analysis in Biological Imaging. *Science* 300(5616), 100–102 (2003)
32. Tran, D., Pham, T., Zhou, X.: Cell Phase Identification using Fuzzy Gaussian Mixture Models. In: *ISPACS 2005, International Symposium on Intelligent Signal Processing and Communication Systems*, Hong Kong, China, December 14–17, 2005, pp. 465–468 (2005)
33. Lieb, J.D., Ortiz de Solorzano, C., Garcia Rodriguez, E., Jones, A., Angelo, M., Lockett, S., Meyer, B.J.: The *Caenorhabditis elegans* Dosage Compensation Machinery Is Recruited to X Chromosome DNA Attached to an Autosome. *Genetics* 156, 1603–1621 (2000)

34. Ecker, R.C., Steiner, G.E.: Microscopy-Based Multicolor Tissue Cytometry at the Single-Cell Level. *Cytometry Part A* 59A, 182–190 (2004)
35. Swedlow, J.R., Goldberg, I., Brauner, E., Sorger, P.K.: Informatics and Quantitative Analysis in Biological Imaging. *Science* 300(5616), 100–102 (2003)
36. Berlage, T.: Analyzing and mining image databases. *DDT* 10(11), 795–802 (2005)
37. Perner, P., Holt, A., Richter, M.: Image Processing in Case-Based Reasoning. *The Knowledge Engineering Review* 20(3), 311–331
38. De Mantaras, R.L., Cunningham, P., Perner, P.: Emergent case-based reasoning applications. *The Knowledge Engineering Review* 20(3), 325–328
39. Holt, A., Bichindaritz, I., Schmidt, R., Perner, P.: Medical applications in case-based reasoning. *The Knowledge Engineering Review* 20(3), 289–292