# Overview of electrical and electronic systems in the vehicle

The amount of electronics in the vehicle has risen dramatically in recent years and is set to increase yet further in the future. Technical developments in semiconductor technology support ever more complex functions with the increasing integration density. The functionality of electronic systems in motor vehicles has now surpassed even the capabilities of the Apollo 11 space module that orbited the Moon in 1969.


## **Overview**

### **Development of electronic systems**


Not least in contributing to the success of the vehicle has been the continuous string of innovations which have found their way into vehicles. Even as far back as the 1970s, the aim was to make use of new technologies to help in the development of safe, clean and economical cars. The pursuit of economic efficiency and cleanliness was closely linked to other customer benefits such as driving pleasure. This was characterized by the European diesel boom, upon which Bosch had such a considerable influence. At the same time, the development of the gasoline engine with gasoline direct injection, which would reduce fuel consumption by comparison with intake-manifold injection, experienced further advancements.

An improvement in driving safety was achieved with electronic brake-control systems. In 1978, the antilock brake system (ABS) was introduced and underwent continual development to such an extent that it is now fitted as standard on every vehicle in Europe. It was along this same line of development that the electronic stability program (ESP), in which ABS is integrated, would debut in 1995.

The latest developments also take comfort into account. These include the hill hold control (HHC) function, for example, which makes it easier to pull away on uphill gradients. This function is integrated in ESP.



K. Reif (Ed.), Fundamentals of Automotive and Engine Technology, DOI 10.1007/978-3-658-03972-1\_13, © Springer Fachmedien Wiesbaden 2014



Many kinds of new functions appear in conjunction with driver-assistance systems. Their scope extends far beyond today's standard features such as Parkpilot or electronic navigation systems. The aim is to produce the "sensitive vehicle" that uses sensors and electronics to detect and interpret its surroundings. Tapping into ultrasound, radar and video sensor technologies has led to solutions that play an important role in assisting the driver, e.g. through improved night vision or distance control.

Value creation structure for the future

The latest studies show that the production costs of an average car will increase only slightly by 2010 despite further innovations. No significant value growth for existing systems is expected in the mechanics/hydraulics domain despite the expected volume growth. One reason here being the electrification of functions that have conventionally been realized mechanically or hydraulically. Brake control systems are an impressive example of this change. While the conventional brake system was characterized more or less completely by mechanical components, the introduction of the ABS brake-control system was accompanied by a greater proportion of electronic components in

the form of sensor technology and an electronic control unit. With the more recent developments of ESP, the additional functions, such as HHC, are almost exclusively realized by electronics.

Even though significant economies of scale are seen with the established solutions, the value of the electrics and electronics will increase overall (Fig. 1). By 2010, this will amount to a good third of the production costs of an average vehicle. This assumption is based not least on the fact that the majority of future functions will also be regulated by electrics and electronics.

The increase in electrics and electronics is associated with a growth in software. Even today, software development costs are no longer negligible by comparison with hardware costs. Software authoring is faced with two challenges arising from the resulting increase in complexity of a vehicle's overall system: coping with the volume and a clearly structured architecture. The Autosar initiative (Automotive Open Systems Architecture), in which various motor vehicle manufacturers and suppliers participate, is working towards a standardization of electronics architecture with the aim of reducing complexity through increased reusability and interchangeability of software modules.

#### Task of an electronic system Open-loop and closed-loop control

The nerve center of an electronic system is the control unit. Figure 3 shows the system blocks of a Motronic engine-management system. All the open-loop and closed-loop algorithms of the electronic system run inside the control unit. The heart of the control unit is a microcontroller with the program memory (flash EPROM) in which is stored the program code for all functions that the control unit is designed to execute.

The input variables for the sequence control are derived from the signals from sensors and setpoint generators. They influence the calculations in the algorithms, and thus the triggering signals for the actuators. These convert into mechanical variables the electrical signals that are output by the microcontroller and amplified in the output stage modules. This could be mechanical energy generated by a servomotor (power-window unit), for example, or thermal energy generated by a sheathed-element glow plug.

#### Communication

Many systems have a mutual influence on each other. For example, it may sometimes be necessary to not only have the electronic stability program carry out a braking intervention in the event wheel spin but also to request that the engine-management system reduce torque and thus counteract wheel spin. Similarly, the control unit for the automatic transmission outputs a request to the engine-management system to reduce torque during a gearshift and thereby promote a soft gear change. To this end, the systems are networked with each other, i.e. they are able to communicate with each other on data buses (e.g. CAN, LIN).

In a premium-class vehicle, there may be up to 80 control units performing their duties. The examples below are intended to give you an insight into the operating principle of these systems.

