



First Master-Permanentization Solution for Telecommunication Tower

Hastining Bagyo Astuti^{1,4}, Rosadi Makhdor^{2,4}, Detriana Margita Sari^{3,4}(✉),
and Soekhatta Setiawan^{3,4}

¹ Operation and Construction Department, Mitratel, Jakarta 12710, Indonesia
Hastining.b.astuti@mitratel.co.id

² Operation and Maintenance Department, Mitratel, Jakarta 12710, Indonesia
720204@telkom.co.id

³ Technology Solution and Operation Improvement, Mitratel, Jakarta 12710, Indonesia
{detriana.margita,soekhatta.setiawan}@mitratel.co.id

⁴ Daya Mitra Telecommunication, Jakarta, Indonesia

Abstract. Telecommunications development in Indonesia is growing rapidly, as it is in other emerging countries. With the expansion of this business, there is a very tight level of competition among Indonesian cellular operators as well as in the Tower Provider sector as a provider of supporting infrastructure services. Furthermore, the demand for infrastructure to support telecommunication systems has increased dramatically over the last decade, as the need to erect more towers. As a consequence, these two factors contribute to an increase in the demand for land to build the new tower. Need a solution to take advantage of the existing site, particularly the guyed mast tower, so that no new land is required. The novelty of this paper presents the First Master solution developed by Mitratel, one of Indonesia's largest tower providers. This solution has been used in several locations and proven to use the existing guyed mast tower without turning off the tower transmission to ensure that the telecoms tower can still function.

Keywords: First Master · Solution · Erection · Tower · Telecom

1 Introduction

Telecommunications is still one of the mainstay businesses, especially in developing countries. Over the past three decades, the technology, standards, and development of the Chinese mobile communications industry have gone through a process of introduction, absorption, digestion, and innovation, and it has already become a leader rather than a follower and a pursuer [1]. Economic growth in Sub-Saharan Africa has been increasing over the last two decades [2]. Adela reports some compelling and robust findings which substantiate that ICT has a statistically significant influence on economic growth in Africa [3]. As evidenced by the tremendous construction of telecommunications tower infrastructure. Considering the explosive services demand in cities as a result of population increase, the need for more support structures to be installed [4]. Because of the increasing need for telecom tower construction, developing countries such as Indonesia

continue to make the telecommunications business a cornerstone. New telecommunication technologies have flooded into Indonesia, within a highly competitive market structure. Local firms such as Telkomsel, Indosat, and Mobile-8 (Smartfren), supported by multinational companies such as Samsung, LG, and Nokia, are now prominent in the market, offering all kinds of discounts on mobile phones and advertising widely [5]. On the other hand, with the growing need for telecommunications infrastructure, there is a limited amount of land available for the building of telecommunications towers. Aside from limited land, there has been an increase in land leasing prices for tower development; the larger the area required, the higher the rent.

However, as building or land permits become more difficult to obtain, aesthetics become increasingly important. Nowadays, it is difficult to find new land to build telecommunications infrastructure, such as towers, so innovation is needed to find new ways to use the existing land and towers while also adding height and new devices. Innovation is complex, uncertain, somewhat disorderly, and subject to changes of many sorts. Innovation is also difficult to measure and demands close coordination of adequate technical knowledge and excellent market judgment to satisfy economic, technological, and other types of constraints – all simultaneously [6]. In this case, related to the telecoms infrastructure, steel is still a commonly used material for steel lattice towers and is typically made from tubular or angular profiles. Steel lattice towers are extensively utilized in the telecommunication industry as supporting structures providing services such as telephoning, wireless internet, or television [7]. Lattice structures for telecommunication purposes are mainly erected in mountainous terrain, where transportation of the building materials can be extremely challenging and costly [8]. When there is a high demand for a specific type of structure, the projects become more unique, with different focus areas from site to site. In addition, because this type of project is now a specialized market, it becomes harder to find real-world experience in terms of both design and execution [9]. Aside from lattice towers, which require specific land, a guyed mast can be used as an alternative solution. Apart from its lightweight, other advantages include the fact that it does not require a significant size of land, the erection time is quicker, and the overall costs are more affordable. Guyed masts have been applied within the field of telecommunications for many years. Previous comparisons of the advantages of guyed masts over self-supporting towers highlight that positive properties of the guyed mast include: lower cost with height, less erection time, and cost-effective foundations [10]. Mitratel, one of Indonesia's largest tower providers provides the solution, to how to use the existing guyed mast structure with minimize strengthening to add more antennas and other ancillaries is called First Master. This solution has been used in several locations and proven to use the existing guyed mast tower without turning off the tower transmission to ensure that the telecoms tower can still function.

2 Background

Telecommunications development in Indonesia is growing rapidly, as it is in other emerging countries. With the expansion of this business, there is a very tight level of competition among Indonesian cellular operators as well as in the Tower Provider sector as a provider of supporting infrastructure services. Furthermore, the demand for infrastructure to support telecommunication systems has increased dramatically over the last decade, as the

need to erect more towers. As a consequence, these two factors contribute to an increase in the demand for land to build the new tower. Nowadays, it is difficult to find new land to build telecommunications infrastructure, such as towers, so innovation is needed to find new ways to use the existing land and towers while also adding height and new devices. Need a solution to take advantage of the existing site, particularly the guyed mast tower, so that no new land is required. Mitratel has the largest tower portfolio in Indonesia spread across strategic locations. Of 35,051 towers, less than 2% or 724 sites are guyed mast structures. Guyed masts are common structures to support telecommunication devices used worldwide. They are slender and light structures frequently exposed to high winds which are determinant loads in their structural design [11]. Guyed masts are telecom towers that have guy wires, which are tensioned cables used to stabilize the tower [12]. Guyed masts are extensively used in the telecommunications industry, and the size, shape, and topology optimization can significantly benefit their transportation and installation [13]. The analysis and design of masts and towers require specific knowledge and expertise, particularly concerning guyed masts. Towers are lightweight structures with high slenderness and high flexibility [11]. This paper presents a solution regarding the use of existing towers especially guyed masts to support demand from operators with additional equipment.

3 Methodology




Used of existing guyed mast structure becomes the main object in this study. The concept of the First Master solution is to keep using the existing guyed mast by modifying by replacing the guyed wire and covering it with steel angle. The purpose of using this steel angle is to ensure that the guyed mast structure can still accept force from either the existing load or an additional load. The guyed mast structure used is 42 m tall, with the following material list below (Table 1):

Table 1. Material List of Guyed Mast.

Member	Material	Dimension	Unit
Horisontal	Roundbar	φ 19	mm
Bracing	Roundbar	φ 19 and φ 16	mm
Leg	Pipe	1	inch

Source: Detail Drawing [14].

Furthermore, to obtain the most efficient tonnage from the use of steel angle, an analysis was performed using the MS Tower version 222 G and this program can be used for linear and non-linear analysis, static and dynamic analysis of communication and transmission towers [15–17]. Standard drawing and drawing modification for the guyed mast is presented below,



DRAWING NO.		REVISIONS	
1	1.000000	1	1.000000
2	1.000000	2	1.000000
3	1.000000	3	1.000000
4	1.000000	4	1.000000
5	1.000000	5	1.000000
6	1.000000	6	1.000000
7	1.000000	7	1.000000
8	1.000000	8	1.000000
9	1.000000	9	1.000000
10	1.000000	10	1.000000
11	1.000000	11	1.000000
12	1.000000	12	1.000000
13	1.000000	13	1.000000
14	1.000000	14	1.000000
15	1.000000	15	1.000000
16	1.000000	16	1.000000
17	1.000000	17	1.000000
18	1.000000	18	1.000000
19	1.000000	19	1.000000
20	1.000000	20	1.000000
21	1.000000	21	1.000000
22	1.000000	22	1.000000
23	1.000000	23	1.000000
24	1.000000	24	1.000000
25	1.000000	25	1.000000
26	1.000000	26	1.000000
27	1.000000	27	1.000000
28	1.000000	28	1.000000
29	1.000000	29	1.000000
30	1.000000	30	1.000000
31	1.000000	31	1.000000
32	1.000000	32	1.000000
33	1.000000	33	1.000000
34	1.000000	34	1.000000
35	1.000000	35	1.000000
36	1.000000	36	1.000000
37	1.000000	37	1.000000
38	1.000000	38	1.000000
39	1.000000	39	1.000000
40	1.000000	40	1.000000
41	1.000000	41	1.000000
42	1.000000	42	1.000000
43	1.000000	43	1.000000
44	1.000000	44	1.000000
45	1.000000	45	1.000000
46	1.000000	46	1.000000
47	1.000000	47	1.000000
48	1.000000	48	1.000000
49	1.000000	49	1.000000
50	1.000000	50	1.000000
51	1.000000	51	1.000000
52	1.000000	52	1.000000
53	1.000000	53	1.000000
54	1.000000	54	1.000000
55	1.000000	55	1.000000
56	1.000000	56	1.000000
57	1.000000	57	1.000000
58	1.000000	58	1.000000
59	1.000000	59	1.000000
60	1.000000	60	1.000000
61	1.000000	61	1.000000
62	1.000000	62	1.000000
63	1.000000	63	1.000000
64	1.000000	64	1.000000
65	1.000000	65	1.000000
66	1.000000	66	1.000000
67	1.000000	67	1.000000
68	1.000000	68	1.000000
69	1.000000	69	1.000000
70	1.000000	70	1.000000
71	1.000000	71	1.000000
72	1.000000	72	1.000000
73	1.000000	73	1.000000
74	1.000000	74	1.000000
75	1.000000	75	1.000000
76	1.000000	76	1.000000
77	1.000000	77	1.000000
78	1.000000	78	1.000000
79	1.000000	79	1.000000
80	1.000000	80	1.000000
81	1.000000	81	1.000000
82	1.000000	82	1.000000
83	1.000000	83	1.000000
84	1.000000	84	1.000000
85	1.000000	85	1.000000
86	1.000000	86	1.000000
87	1.000000	87	1.000000
88	1.000000	88	1.000000
89	1.000000	89	1.000000
90	1.000000	90	1.000000
91	1.000000	91	1.000000
92	1.000000	92	1.000000
93	1.000000	93	1.000000
94	1.000000	94	1.000000
95	1.000000	95	1.000000
96	1.000000	96	1.000000
97	1.000000	97	1.000000
98	1.000000	98	1.000000
99	1.000000	99	1.000000
100	1.000000	100	1.000000

Fig. 1. Existing Guyed Mast. Modification Guyed Mast

Fig. 2. Outline Drawing

Figure 1 show the original Guyed Mast modification, the modifications include removing the guy wire and replacing it with a steel angle, popularly known as Self Supporting Tower (SST) [18]. Figure 2 shows the material list for Guyed Mast and the modification or SST. Figure 3 presented a view of the guayed mast including detail of the connection. Before undertaking a guayed mast modification with SST, make sure the guy wire is tight [19]. To keep the guy wire, a Helical pile will be installed immediately, this function as a temporary foundation to attach those guy wire to it [19]. Helical piles are now widely used in many fields, both onshore and offshore, and have proven to be very useful and efficient. Large diameter piles at cohesive and cohesionless sites in western Canada using three-helix were successfully implemented [20]. Helical piles are used mainly to resist tension forces generated by uplift and overturning moments of various structures, therefore they have been suggested as a potential alternative to driven piles as offshore piles because they provide a large uplift capacity due to the anchor effect of the helix [20]. M. Muthukumar and Sanjay Kumar Shukla also did deep research regarding the use of Helical piles in expansive soil [21]. Tests were carried out on helical pile foundations where there were similarities between helical collisions and pile collisions [22].

To get a better understanding, will explain how the Helical pile is used to support this solution.




Fig. 3. Guyed Mast view.

Figures 4 and 5 show the Guyed mast 42 m high view and section which will be permanently modified into SST 42 m using the existing guyed mast. Figure 6 presented a strengthening plan using a Helical pile to keep the Guyed mast still standing during the transformation from Guyed mast to SST.

The general process regarding the First master is already described in the paragraph above, furthermore, the picture below will present all processes or activities starting from beginning until finish. Starting from the fabrication process, site opening, using Helical pile, pouring concrete for a new foundation, tower installation, and finally equipment installation on the existing Guyed mast site without dismantling and shutting down the power (Fig. 7).




Fig. 4. Guyed Mast section.




Fig. 5. Strengthening plan with Helical pile [23, 24]




Fig. 6. Detail of Helical Pile [23, 24]




Fig. 7. The first Master construction process is on-site [25].

4 Conclusion

The first master staging consists of the following milestones as shown in the Table below (Table 2):

Table 2. First master Stages.

First period	Second period	Third period
Guyed mast Permanentization planning Overload and over quota database for Guyed mast tower	Review and design selection Approval for design Tower first master mockup	Tower’s first master fabrication Delivery to site Tower implementation

Each of the milestones completed shows that there is a difference in duration/time between the first master and the standard process. In general, the first master approach is 24 days faster than the conventional method (Built to Suite or B2S). The following figure shows the time difference between First Master and the typical B2S method (Fig. 8):

Timeline Planning-Actual **FIRST MASTER** vs Standard B2S

ACTIVITY	PLANNING	ACTUAL	REMARKS
SITAC	35	41	PROGRAM FIRST MASTER
Survey, Soil Test & Design	10	7	Design 4 Tenant Operator
Community information	5	4	Local Community, Local Government, Land Lord
Permit and legal aspect	20	30	Permit and legal aspect
Construction	70	54	
Fabrication	30	21	Horizontal check
Construction	40	33	Construction
TOTAL DURATION TIME	105	95	

V

S

ACTIVITY	PLANNING	REMARKS
SITAC-SIS B2S	44	B2S (New Site)
SIS, Soil Test & Design	14	
Community information	5	Process of Site Acquisition new site
Permit and legal aspect	25	
CME B2S	75	
Fabrication	30	Implementation process new site
Construction	45	Construction process
TOTAL DURATION TIME	119	

Fig. 8. Time Planning Actual First Master vs Standard [25]

Aside from the reduced time duration, the other benefits of the First Master solution are described in the figure below (Fig. 9).

NO	Scope of Work	FIRST MASTER	STANDARD TOWER (SST 4 LEG/3LEG)
1	Land lease for support Combat (Max 3 month)	No Need	Need
2	Combat	No Need	Need
3	Dismantle Equipment	No Need Equipment On at Tower GM-Existing	No Need
4	Dismantle Tower	No Need	Need – New Tower installation
5	Dismantle Sling	No Need	Need – New Tower installation
6	SACME	Need	Need
7	RPI-On Air Equipment	Easy to move the equipment directly	Equipment move after Erection Tower (RPI) done
8	Structural point of view	From Guyed Mast to 4 Leg tower Design calculation suitable for tenant capacity or existing Load	Standard Tower SST (4 Leg-3 Leg) Design calculation base on type of tower (New Light, Light, Medium, Back Bone)
9	Pro - Contra	No turn off equipment No new land Easy to move existing equipment Structural design more flexible and suitable for existing load	Turn off equipment Tower existing mandatory to dismantle New land Structural design refer to standard design
10	Equipment	4 Tenant : Ø 1.2 MW (8 Pcs) - 2.580 x 0.260 x 0.120 Antenna Sector (12 Pcs) - 0.550 x 0.550 x 0.150 RRU (24 Pcs)	2 Tenant (6RF + 6RRU + 2MW 0.6m + 1MW 1,2m)

Fig. 9. First Master Pro Cont [25].

We realize that the first master is not ideally yet; further improvements are required to ensure that this solution is truly the best answer in terms of implementation method, cost, and time.

References

1. Qin, H.: Chapter 7 from follower to leader: China and THE. World Sci. 117–134 (2013)
2. Donou-Adonsou, F., Lim, S., Mathey, S.A.: Technological progress and economic growth in Sub-Saharan Africa: evidence from telecommunications infrastructure. *Int. Adv. Econ. Res.* **22**(1), 65–75 (2016)
3. Adeleye, N., Eboagu, C.: Evaluation of ICT development and economic growth in Africa. *NETNOMICS Econ. Res. Electron. Netw.* (2019)
4. Tsavdaridis, K.D., Nicolaou, A., Mistry, A.D., Efthymiou, E.: Topology optimisation of lattice telecommunication tower and performance-based design considering wind and ice loads. *Structures* **27**, 2379–2399 (2020)
5. McCawley, P.: Infrastructure policy in Indonesia, 1965–2015: a survey. *Bull. Indones. Econ. Stud.* **51**(2), 263–285 (2015)
6. Kline, S.J.: An overview of innovation. *Stud. Sci. Innov. Process* 173–204 (2009)
7. Szafran, J.: An experimental investigation into failure mechanism of a full-scale 40 m high steel telecommunication tower. *Eng. Fail. Anal.* **54**, 131–145 (2015)
8. Spiliopoulos, A., Dasiou, M.E., Thanopoulos, P., Vayas, I.: Experimental tests on members made from rolled angle sections. *Steel Constr.* **11**(1), 84–93 (2018)
9. Holmström, P., Nielsen, M.G., Lindgren, O.: Replacement of two 320 m masts in Sweden. *Ce/Papers* **3**(3–4), 791–796 (2019)
10. Jespersen, M., Støttrup-Andersen, U.: Guyed wind turbine towers: developments and outlook. *Ce/Papers* **3**(3–4), 779–784 (2019)
11. Elena Parnás, V., Martín Rodríguez, P., Castañeda Hevia, A.E.: Structural behavior of guyed mast with asymmetrical anchors. *J. Braz. Soc. Mech. Sci. Eng.* **35**(2), 61–67 (2013)
12. Cucuzza, R., Rosso, M.M., Aloisio, A., Melchiorre, J., Lo Giudice, M., Marano, G.C.: Size and shape optimization of a guyed mast structure under wind, ice and seismic loading. *Appl. Sci.* **12**(10) (2022)
13. Travanca, R., Varum, H., Vila Real, P.: The past 20 years of telecommunication structures in Portugal. *Eng. Struct.* **48**, 472–485 (2013)
14. Mitratel: 2021 Structural analysis of SST 42m (permanenization of existing guyed mast 42m) (2021)
15. Saudi, G.: Structural assessment of a guyed mast through measurement of natural frequencies. *Eng. Struct.* **59**, 104–112 (2014)
16. A./TIA, TIA-222-G: Structural standard for antenna supporting structures and antennas
17. Meshmesha, H.M., Kennedy, J.B., Sennah, K., Moradi, S.: Static and dynamic analysis of guyed steel lattice towers. *Struct. Eng. Mech.* **69**(5), 567–577 (2019)
18. Pte, T.I., Page, C.: Standard operating procedure (SOP) for the replacing or re-positioning turnbuckles installed to guyed masts. *Poles Tool Box Talks*, pp. 7–11
19. Li, W., Zhang, D.J.Y., Sego, D.C., Deng, L.: Field testing of axial performance of large-diameter helical piles at two soil sites. *J. Geotech. Geoenviron. Eng.* **144**(3), 2–6 (2018)
20. Spagnoli G., de Hollanda Cavalcanti Tsuha, C.: A review on the behavior of helical piles as a potential offshore foundation system. *Mar. Georesour. Geotechnol.* **38**(9), 1013–1036 (2020)
21. Muthukumar, M., Shukla, S.K.: Comparative study on the behaviour of granular pile anchors and helical pile anchors in expansive soils subjected to swelling. *Int. J. Geotech. Eng.* **14**(1), 49–54 (2020)
22. Elkasabgy, M., El Nagggar, M.H.: Lateral vibration of helical and driven steel piles installed in clayey soil. *J. Geotech. Geoenviron. Eng.* **144**(9), 1–8 (2018)
23. Mitratel: Temporary support for existing guyed mast foundation. no. Option 02
24. Mitratel: Temporary support foundation design report of existing guyed mast 42 m checked by: Gin Gin Ginanjar (2020)
25. Mitratel O&M Team: First master site gonggang magetan, installation permanentization GM to SST 42 (2021)