



# Evaluation of thermal storage system during freezing and loading nano-powders

Bandar Almohsen<sup>1</sup>

Received: 24 September 2023 / Accepted: 16 March 2024 / Published online: 27 May 2024  
© The Author(s) 2024

## Abstract

In pursuit of advancing the efficiency of cold energy storage, a uniquely designed curved container has been employed, filled with a water-nanoparticle mixture. The container is equipped with fins, strategically leveraging the enhanced conduction facilitated by the presence of nanoparticles. The simulation of the intricate unsteady phenomena in this study has been conducted using the finite element technique, providing a robust analytical framework. The incorporation of an adaptive grid ensures a refined resolution, particularly in the vicinity of the ice front region. The nanoparticle fraction ( $\phi$ ) emerges as a pivotal factor directly influencing the rate of solidifying. The dispersion of nano-powders leads to a noteworthy reduction in completion time, demonstrating a substantial 33.21% improvement. The diameter of the nano-powders ( $d_p$ ) introduces diverse effects on the solidification process, primarily due to its significant influence on the conductivity of the nanomaterial. An in-depth exploration of the impact of  $d_p$  reveals compelling insights. As the  $d_p$  increases from its smallest size to 40 nm, there is a commendable 15.12% reduction in the required freezing time. However, a subsequent increment in  $d_p$  beyond this threshold results in a notable 36.56% increase in the freezing time. The findings presented here not only contribute to the fundamental understanding of freezing processes but also hold practical implications for the design and optimization of cold storage systems.

**Keywords** Transient phenomena · Solidification · FEM · Curved finned tank · Nanomaterial

## Introduction

An effective solution to mitigate the alternating of energy lies in the use of latent heat storage units employing PCM (Phase Change Materials) [1–4]. Such units are frequently regarded as a highly efficient technology to bridge the gap between supply and demand of energy [5–8]. Based on the published literature on evaluating the productivity of these tools, selecting the most suitable tool remains an issue and perplexing endeavor [9–12], particularly when dealing with hybrid techniques involving the application of multiple enhancement strategies. Currently, the hybrid approach stands out as the most popular and extensively adopted improvement strategy due to its associated benefits [13–16]. Nevertheless, the challenge of designing and selecting compatible improvement methods that work synergistically has

become increasingly complex [17–20]. For instance, challenges such as the extraordinary price of nanoparticles and their preparation, and technical difficulties associated with the design and manufacturing of TES systems that incorporate additional surface areas like permeable foams and fins [21–24]. Additionally, the incorporation of fins, permeable zone, or heat pipes may diminish free convection, thereby compromising the overall performance, as these elements occupy space that could otherwise be filled by PCM [25–28]. Yagci and team [29] conducted an experimental exploration of the complete cycle of paraffin within a vertical annular free space. Their outputs exposed that the addition of fins to the tube caused in a 29.8% decrement in the total freezing time compared to the case without fins. Sheikholeslami [30] explored the integration of a paraffin container with a PVT system. To enhance the electrical productivity of the system, he incorporated MWCNT nano-powders.

Castell et al. [31] investigated the impact of fins on melting of PCM. They conducted an experimental comparison and demonstrated that the install of fins declined the time required for heat transfer from the PCM to the water. In

✉ Bandar Almohsen  
balmohsen@ksu.edu.sa

<sup>1</sup> Department of Mathematics, College of Science, King Saud University, P.O.Box 2455, Riyadh 11451, Saudi Arabia

a collaborative effort between two laboratories in Iran and Italy, researchers delved into the productivity of PVT units and analyzed the detrimental effects of dust [32]. Subsequently, the same research group [33] proposed the utilization of nanofluid as a spectral filter and sustainable thermoelectrics to augment system productivity. Kozelj et al. [34] conducted a comparison among a traditional unit and hybrid storage unit. They showed that performance of hybrid unit enhances about 70%. In an effort to mitigate the detrimental effects of dust and improve system efficiency, Sheikholeslami et al. [35] employed a self-cleaning coating and NEPCM. The proposed structure has potential applications for building ventilation. Deng et al. [36] scrutinized a research to investigate the impact of the number and organization of fins on enhancing the melting rate of PCM in a circular configuration. They demonstrated a correlation to achieve optimal outputs. Sheikholeslami and Khalili [37, 38] harnessed various nanoparticle types with the aim of boosting the efficiency of solar panels. Their application of nanofluid extends beyond mere cooling, encompassing its role as a spectral filter as well. Acir and Canli [39] conducted experimental investigations on the charging process of paraffin with multiple fins under simulated irradiation. The researchers observed that the improvement ratio of the melting rate increased with a decrease in fin thickness, and typically, there was an optimal number of fins to maximize melting efficiency. Attempting to harness solar irradiation, Sheikholeslami [40] explored a novel system utilizing hot fluid in a double-pipe configuration, incorporating a paraffin zone for energy conservation. The outcomes designated that the utilization of a mixture of nano-powders and paraffin exhibited superior performance.

This research examines into the simulation of the solidification process of water within a uniquely designed curved container with integrated fins. The key innovation lies in the incorporation of nanoparticles to augment the cold storage process. Leveraging a numerical simulation approach based on the FEM with an adaptive mesh adds a layer of sophistication to the study, allowing for a more accurate simulation. Novelty in this work is evident in the meticulous consideration of various factors, treating additives with different concentrations and diameters as variables. The governing equations were intelligently simplified, focusing specifically on the freezing process while omitting the influence of velocity. The visual representation of simulation outcomes through contours and plots contributes to a more comprehensive understanding of system behavior under diverse conditions. In comparison with previous publications, the significance of this study becomes apparent. While existing research has explored freezing processes to some extent, the integration of nanoparticles and the meticulous consideration of variable factors represent a notable research gap. This study, therefore, not only builds upon existing knowledge but introduces a novel perspective,

addressing a crucial aspect of cold storage efficiency. The importance of this research cannot be overstated. In various applications, from industrial settings to technological advancements, optimizing cold storage is of paramount importance. The ability to accelerate the freezing process, as demonstrated through the introduction of nanoparticles and the thoughtful consideration of variable factors, has practical implications for energy efficiency, resource management, and the overall performance of systems relying on cold storage. In essence, this study contributes to the broader understanding of freezing dynamics and establishes a foundation for more effective and efficient cold storage methodologies.

## The description of cold storage unit

In this research, the acceleration of the freezing process is accomplished by presenting nanomaterial of varying sizes into the container, as depicted in Fig. 1. Excluding velocity terms and employing a single-phase preparation, the modeling strategy yields the definitive unsteady model. Current numerical tool allows for an in-depth investigation into the influence of nanoparticle characteristics on freezing. The ultimate transient equations take the following form [41]:

$$(\rho C_p)_{nf} \frac{dT}{dt} = \nabla(k_{nf} \nabla T) + L_{nf} \frac{dS}{dt} \quad (1)$$






Fig. 1 Freezing within curved tank

**Fig. 2** Style of grid with promotion of time



**Fig. 3** Testing accuracy of code [42]



**Fig. 4** Increment of freezing with augment of  $\phi$




Fig. 4 (continued)








Fig. 4 (continued)



$$\varphi = k_p/k_f, \frac{k_{nf}}{k_f} = 1 - 3 \frac{(1 - \varphi)\phi}{(1 - \varphi)\phi + (\varphi + 2)} + 5 \times 10^4 \left( \frac{d_p \rho_p}{T \kappa_b} \right)^{-0.5} c_{p,f} g'(d_p, T, \phi) \phi \rho_f \tag{6}$$

In Eq. (6), the interplay between nano-powder size and nanoparticle concentration ( $\phi$ ) is evident. The solution to these equations is achieved through numerical techniques, specifically employing the finite element method along with an implicit approach and adaptive grid. This simulation methodology, founded by Sheikholeslami [41], has become a widely adopted practice for demonstrating the freezing process, finding widespread application in various publications.

Fig. 5 Superior  $\phi$  and progress of ice front

$$\begin{cases} S = 1 & (T - T_m) < (-T_0) \\ S = 0 & (T - T_m) > (-T_0) \\ S = (T_m + 0.5T_0 - T)/T_0 & (-T_0) < (T - T_m) < T_0 \end{cases} \tag{2}$$

Through the application of an implicit method, the discretization of transient terms has been accomplished. The nanomaterial's formulation is applicable under the assumption of a uniform distribution of nanoparticles within the spatial domain [41]:


$$(L\rho)_{nf} = (L\rho)_f(1 - \phi) \tag{3}$$

$$\rho_{nf} = (1 - \phi)\rho_f + \phi\rho_p \tag{4}$$

$$(\rho C_p)_{nf} = (\rho C_p)_f(1 - \phi) + (\rho C_p)_p \phi \tag{5}$$

### Results and discussion

In this investigation, cold storage was simulated within a specially designed curved container equipped with fins, aiming to expedite cold storage. To enhance the cold storage efficiency, nanoparticles were introduced in addition to fins. The study employed a numerical simulation approach based on the FEM. Various factors, including additives with different concentrations and diameters, were treated as variables in the investigation. Governing equations for the freezing process were simplified by disregarding the impact of velocity. Simulation outcomes were visually presented through contours and plots, offering a comprehensive understanding of system behavior under different conditions. Furthermore, the time required for complete freezing was calculated for each case, serving as a critical metric directly related to the rate of cold storage. This comprehensive approach not only advances the understanding of freezing processes but also underscores the practical implications of optimizing cold storage, a critical aspect in various applications.



**Fig. 6** Values of scalars for different levels of time and  $\phi$

The adaptive grid has been employed, representing a valuable technique for achieving high modeling accuracy in unsteady processes, particularly those involving phase change. The grid style for different time steps is illustrated in Fig. 2, revealing that the number of elements around the solid front is superior to that in other areas. This strategic distribution ensures that regions with higher temperature gradients have more nodes, enhancing the accuracy of the modeling process. To demonstrate the code's reliability and reasonable accuracy, a reproduction of previous benchmark work in the same field has been executed, and the outputs are presented in Fig. 3 [42]. The method employed exhibits good adaptability, making the code suitable for application in the current study. This validation

process instills confidence in the accuracy and fidelity of the numerical approach adopted in the present article.

To illustrate the influence of  $\phi$  on the cold storage process, Figs. 4, 5, and 6 are presented. The solid fraction, denoted as  $S$ , exhibits an increasing trend with the elevation of  $\phi$ . Consequently, a greater proportion of the solid phase appears within the container, leading to a colder system. It is noteworthy that the energy of the system decreases as the concentration of additives upsurges. The ice front also moves at a faster rate in cases with higher  $\phi$ . Examining the variation in  $\phi$  from 0 to 0.02 and 0.04, the required freezing time changes from 4.35 s to 3.47 s and 2.9 s, respectively. These findings elucidate the direct relationship between  $\phi$  and the efficiency of the cold

**Fig. 7** Alternation of freezing with involving various  $d_p$






Fig. 7 (continued)






Fig. 7 (continued)

Fig. 8 Greater  $d_p$  and progress of ice front

storage process, underscoring the potential for optimizing the system by carefully manipulating the concentration of additives.

Variations in  $d_p$  exert a significant influence on the freezing process, as depicted in Figs. 7–9. The observed outcomes underscore the impact of employing additives of different sizes on the freezing dynamics. Consequently, identifying the optimized size that yields the highest cold storage rate becomes a crucial consideration. In this section of the article, three levels of  $d_p$  are explored. The parameter  $T$ , representing the completion time, exhibits a decreasing trend over time, while  $S$ , indicative of the solidification rate, demonstrates an increasing tendency. Notably, for

$d_p = 40$  nm, the system reaches its highest  $S$  at a lower time level, highlighting the superior performance of such particles. The minimum value of  $T$  is achieved when  $d_p = 40$  nm. Examining the variation in  $d_p$  from the minimum level to 40 nm and the greatest level, the required time shifts from 3.42 s to 2.9 s and 3.96 s, respectively. These results provide valuable insights into the nuanced relationship between  $d_p$  and freezing time, contributing to the optimization of cold storage efficiency.

Figure 10 illustrates the impact of variables on the required freezing time. The introduction of nano-powders into water results in an enhanced freezing rate due to the increased conduction mode. In the context of cold storage, where conduction serves as the primary mechanism, any factor promoting heightened conductivity leads to a reduction in process time. The parameter  $\phi$  exhibits a reverse relationship with the required time, with an optimal size identified for  $d_p$  at the second level of this factor. Specifically, when  $\phi = 0.04$ , an increase in  $d_p$  initially leads to a 15.12% decrease in completion time, followed by a subsequent 36.56% increase. Similarly, when  $\phi = 0.02$ , the process time initially decreases by 9.89% with  $d_p$  growth and subsequently increases by 22%. In the lack of additives, the phenomena take 4.35 s to achieve full freezing, while the introduction of nanomaterial reduces this time significantly to 2.9 s, indicating a noteworthy 33.21% increase in the freezing rate. Notably, the impact of  $\phi$  is most pronounced for medium-sized particles, with  $d_p = 50$  nm showing the least variation with an increase in  $\phi$ . Considering the range of  $\phi$  from 0 to its maximum level, the freezing time experiences a reduction of about 21.31% and 8.79% for  $d_p$  values of 30 and 50 nm, respectively. These results emphasize the intricate relationship between  $\phi$ ,  $d_p$ , and freezing time,





Fig. 9 Values of scalars for different levels of time and  $d_p$

**Fig. 10** Change of rate of freezing with change of two variables



providing valuable insights for optimizing the efficiency of cold storage systems.

## Conclusions

Current attempt involved simulating the freezing process of water within a container featuring a curved design and integrated fins. The acceleration of cold storage was achieved through the incorporation of nanoparticles in conjunction with fins. The numerical simulation, based on the FEM and incorporating an adaptive grid, presented another dimension to the current investigation. The additives exhibited diverse concentrations and diameters, which were treated as variables in the study. Governing equations were streamlined to account for the freezing process, with the neglect of velocity impact. The outcomes were visualized through contours and plots, showcasing the impact of various concentrations and diameters. Additionally, the required time for complete freezing was determined for each scenario, emerging as a key determinant of cold storage efficiency. This comprehensive exploration contributes valuable insights into optimizing freezing dynamics. The primary driving force governing the cold storage process is conduction, wherein any factor promoting increased conductivity corresponds to a reduction in process time. The infusion of nano-powders into water serves to elevate the freezing rate by amplifying the conduction mode. The parameter  $\phi$  exhibits an inverse correlation with the required time for freezing. As  $\phi$  escalates from 0 to its maximum level, there is a notable 21.31% and 8.79% decrease in freezing time for  $dp$  values of 30 and 50 nm, respectively. In the absence of additives, the process takes 4.35 s to achieve full freezing. However, with the introduction of nanomaterials, this time significantly decreases to 2.9 s, signifying a remarkable 33.21% increase in the freezing rate. The impact of  $\phi$  is most pronounced for medium-sized particles, with  $dp = 50$  nm exhibiting the least variation with increasing  $\phi$ . Concerning  $dp$ , the results reveal the existence of an optimal size, particularly at the second level of this factor. When  $\phi = 0.04$ , the completion time experiences an initial 15.12% decrease followed by a subsequent 36.56% increase as  $dp$  augments. The temperature ( $T$ ) demonstrates a decreasing trend over time, while the solidification front position ( $S$ ) exhibits an increasing tendency. The case with  $dp = 40$  nm attains the highest  $S$  at a lower time level, indicating superior performance for such particles. In conclusion, the intricate interplay of  $\phi$  and  $dp$  in the freezing process underscores the need for meticulous parameter selection to optimize the efficiency of cold storage systems. The findings not only contribute to a deeper thoughtful of freezing but also

provide practical insights for the design and enhancement of cold storage technologies.

**Acknowledgements** This research is supported by Researchers Supporting Project Number (RSP2024R158), King Saud University, Riyadh, Saudi Arabia.

**Data availability statement** No datasets were generated or analyzed during the current study.

## Declarations

**Conflict of interest** There is no conflict of interest regarding to this manuscript.

**Open Access** This article is licensed under a Creative Commons Attribution 4.0 International License, which permits use, sharing, adaptation, distribution and reproduction in any medium or format, as long as you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons licence, and indicate if changes were made. The images or other third party material in this article are included in the article's Creative Commons licence, unless indicated otherwise in a credit line to the material. If material is not included in the article's Creative Commons licence and your intended use is not permitted by statutory regulation or exceeds the permitted use, you will need to obtain permission directly from the copyright holder. To view a copy of this licence, visit <http://creativecommons.org/licenses/by/4.0/>.

## References

1. Almarashi A, Alrahal DM, Al-Bonsrulah HAZ, Hamali W, Mechai I, Yahya Almusawa M, Egami RH. Effect of loading  $Fe_3O_4$  nanoparticles on electrical performance of solar panel utilizing numerical modeling. *Case Stud Therm Eng.* 2024;55:104165. <https://doi.org/10.1016/j.csite.2024.104165>.
2. Xiong P-Y, Almarashi A, Dhahad HA, Alawee WH, Issakhov A, Chu Y-M. Nanoparticles for phase change process of water utilizing FEM. *J Mol Liq.* 2021;334:116096. <https://doi.org/10.1016/j.molliq.2021.116096>.
3. Sheikholeslami M, Al-Hussein HRA. Modification of heat storage system involving Trombe wall in existence of paraffin enhanced with nanoparticles. *J Energy Storage.* 2023;58:106419. <https://doi.org/10.1016/j.est.2022.106419>.
4. Rothan YA. Roles of nanoparticles on freezing process of water within a tank equipped within fins. *J Mol Liq.* 2021;337(1):116491. <https://doi.org/10.1016/j.molliq.2021.116491>.
5. Chu Y-M, Yadav D, Shafee A, Li Z, Bach Q-V. Influence of wavy enclosure and nanoparticles on heat release rate of PCM considering numerical study. *J Mol Liquids.* 2020;319:114121. <https://doi.org/10.1016/j.molliq.2020.114121>.
6. Sheikholeslami M. Analyzing melting process of paraffin through the heat storage with honeycomb configuration utilizing nanoparticles. *J Energy Storage, Part B.* 2022;52: 104954. <https://doi.org/10.1016/j.est.2022.104954>.
7. Rothan YA. Investigation of hybrid nanomaterial application in melting process of paraffin enhanced with nanoparticles. *Phys Scr.* 2021. <https://doi.org/10.1088/1402-4896/ac3877>.
8. Li S, Wang F, Ouyang L, Chen X, Yang Z, Rozga P, Fogana I. Differential low-temperature AC breakdown between synthetic ester and mineral oils: insights from both molecular dynamics and quantum mechanics. *IEEE Trans Dielectr Electr Insul.* 2023. <https://doi.org/10.1109/TDEI.2023.3345299>.



9. Chu Y-M, Hajizadeh MR, Li Z, Bach Q-V. Investigation of nano powders influence on melting process within a storage unit. *J Mol Liquids*. 2020;318:114321. <https://doi.org/10.1016/j.molliq.2020.114321>.
10. Babazadeh H, Muhammad T, Shakeriaski F, Ramzan M, Hajizadeh MR. Nanomaterial between two plates which are squeezed with impose magnetic force. *J Therm Anal Calorim*. 2020. <https://doi.org/10.1007/s10973-020-09619-6>.
11. Rothan YA. Modeling for freezing of PCM enhanced with nano-powders within a duct. *Eur Phys J Plus*. 2022;137:573. <https://doi.org/10.1140/epjp/s13360-022-02505-0>.
12. Kuang W, Wang H, Li X, Zhang J, Zhou J, Zhao Y. Application of the thermodynamic extremal principle to diffusion-controlled phase transformations in Fe–C–X alloys: modeling and applications. *Acta Mater*. 2018;159:16–30. <https://doi.org/10.1016/j.actamat.2018.08.008>.
13. Chu Y-M, Abu-Hamdeh NH, Ben-Beya B, Reza Hajizadeh M, Li Z, Bach Q-V. Nanoparticle enhanced PCM exergy loss and thermal behavior by means of FVM. *J Mol Liquids Part B*. 2020;320:114457. <https://doi.org/10.1016/j.molliq.2020.114457>.
14. Basha H, Sivaraj R. Stability analysis of Casson nanofluid flow over an extending/contracting wedge and stagnation point. *J Appl Comput Mech*. 2022;8(2):566–79. <https://doi.org/10.22055/jacm.2020.32618.2045>.
15. Manh TD, Salehi F, Shafee A, Nam ND, Shakeriaski F, Babazadeh H, Vakkari A, Tlili I. Role of magnetic force on the transportation of nano powders including radiation. *J Therm Anal Calorim*. 2019. <https://doi.org/10.1007/s10973-019-09182-9>.
16. Hasan PMZ, Abu-Hamdeh NH, Nusier OK, Milyani AH, Al-Bonsrulah HAZ, Elbashir NBM. Management of period of solidification with loading nanoparticles simulating unsteady heat transfer. *Case Stud Therm Eng*. 2024;53:103928. <https://doi.org/10.1016/j.csite.2023.103928>.
17. Yang S, Huang Z, Hu Q, Zhang Y, Wang F, Wang H, Shu Y. Proportional optimization model of multiscale spherical BN for enhancing thermal conductivity. *ACS Appl Electron Mater*. 2022;4(9):4659–67. <https://doi.org/10.1021/acsaelm.2c00878>.
18. Wang T, Almarashi A, Al-Turki YA, Abu-Hamdeh NH, Hajizadeh MR, Chu Y-M. Approaches for expedition of discharging of PCM involving nanoparticles and radial fins. *J Mol Liquids*. 2020. <https://doi.org/10.1016/j.molliq.2020.115052>.
19. Milyani AH, Abu-Hamdeh NH, Azhari AA, Al-Bonsrulah HAZ, Alghawli AS. Acceleration the solidification process of cold-thermal storage/nanoparticles using finned container: a numerical study. *Case Stud Therm Eng*. 2023;51:103647. <https://doi.org/10.1016/j.csite.2023.103647>.
20. Chen Y, Wang G, Song L, Shen X, Wang J, Huo J, Nie Q. Unraveling the crystallization kinetics of supercooled liquid GeTe by ultrafast calorimetry. *Cryst Growth Des*. 2017;17(7):3687–93. <https://doi.org/10.1021/acs.cgd.7b00259>.
21. Othman HA, Rguigui H, Altoum SH, Elamin MA. Nanomaterial efficacy on freezing of PCM with involvement of numerical simulation. *J Mol Liquids*. 2022;362:119658. <https://doi.org/10.1016/j.molliq.2022.119658>.
22. Magodora M, Mondal H, Sibanda P. Effect of Cattaneo–Christov heat flux on radiative hydromagnetic nanofluid flow between parallel plates using spectral quasilinearization method. *J Appl Comput Mech*. 2022;8(3):865–75. <https://doi.org/10.22055/jacm.2020.33298.2195>.
23. Li Y, Shakeriaski F, Barzinjy AA, Dara RN, Shafee A, Tlili I. Nanomaterial thermal treatment along a permeable cylinder. *J Therm Anal Calorim*. 2020;139:3309–15. <https://doi.org/10.1007/s10973-019-08706-7>.
24. Long X, Chong K, Su Y, Du L, Zhang G. Connecting the macroscopic and mesoscopic properties of sintered silver nanoparticles by crystal plasticity finite element method. *Eng Fract Mech*. 2023;281: 109137. <https://doi.org/10.1016/j.engfracmech.2023.109137>.
25. Sheikholeslami M. Modeling investigation for energy storage system including mixture of paraffin and ZnO nano-powders considering porous media. *J Petrol Sci Eng*. 2022;219: 111066. <https://doi.org/10.1016/j.petrol.2022.111066>.
26. Rothan YA. Numerical approach for melting of paraffin inside a duct containing multi sinusoidal PCM containers. *J Petrol Sci Eng*. 2022;212: 110351. <https://doi.org/10.1016/j.petrol.2022.110351>.
27. Xiao D, Liu M, Li L, Cai X, Qin S, Gao R, Li G. Model for economic evaluation of closed-loop geothermal systems based on net present value. *Appl Therm Eng*. 2023;231: 121008. <https://doi.org/10.1016/j.applthermaleng.2023.121008>.
28. Qin Y. Numerical modeling of energy storage unit during freezing of paraffin utilizing Al<sub>2</sub>O<sub>3</sub> nanoparticles and Y-shape fin. *J Energy Storage Part B*. 2021;44: 103452. <https://doi.org/10.1016/j.est.2021.103452>.
29. Yagci OK, Avci M, Aydin O. Melting and solidification of PCM in a tube-in-shell unit: effect of fin edge lengths' ratio. *J Energy Storage*. 2019;24: 100802.
30. Sheikholeslami M. Numerical investigation for concentrated photovoltaic solar system in existence of paraffin equipped with MWCNT nanoparticles. *Sustain Cities Soc*. 2023;99: 104901. <https://doi.org/10.1016/j.scs.2023.104901>.
31. Castell A, Solé C, Medrano M, Roca J, Cabeza LF, García D. Natural convection heat transfer coefficients in phase change material (PCM) modules with external vertical fins. *Appl Therm Eng*. 2008;28(13):1676–86.
32. Sheikholeslami M, Khalili Z, Scardi P, Ataollahi N. Concentrated solar photovoltaic cell equipped with thermoelectric layer in presence of nanofluid flow within porous heat sink: impact of dust accumulation. *Sustain Cities Soc*. 2023;98: 104866. <https://doi.org/10.1016/j.scs.2023.104866>.
33. Sheikholeslami M, Khalili Z, Scardi P, Ataollahi N. Environmental and energy assessment of photovoltaic-thermal system combined with a reflector supported by nanofluid filter and a sustainable thermoelectric generator. *J Clean Prod*. 2024;438(20): 140659. <https://doi.org/10.1016/j.jclepro.2024.140659>.
34. Koželj R, Mlakar U, Zavrl E, Stritih U, Stropnik R. An experimental and numerical analysis of an improved thermal storage tank with encapsulated PCM for use in retrofitted buildings for heating. *Energy Build*. 2021;248: 111196. <https://doi.org/10.1016/j.enbuild.2021.111196>.
35. Sheikholeslami M, Khalili Z, Mousavi SJ. Influence of self-cleaning coating on performance of photovoltaic solar system utilizing mixture of phase change material and graphene nanoparticle. *J Build Eng*. 2023;77(15): 107540. <https://doi.org/10.1016/j.jobee.2023.107540>.
36. Deng S, Nie C, Jiang H, Ye W-B. Evaluation and optimization of thermal performance for a finned double tube latent heat thermal energy storage. *Int J Heat Mass Transf*. 2019;130:532–44.
37. Sheikholeslami M, Khalili Z. Solar photovoltaic-thermal system with novel design of tube containing eco-friendly nanofluid. *Renew Energy*. 2024;222:119862. <https://doi.org/10.1016/j.renene.2023.119862>.
38. Sheikholeslami M, Khalili Z. Simulation for impact of nanofluid spectral splitter on efficiency of concentrated solar photovoltaic

- thermal system. *Sustain Cities Soc.* 2024;101: 105139. <https://doi.org/10.1016/j.scs.2023.105139>.
39. Acir A, Canli ME. Investigation of fin application effects on melting time in a latent thermal energy storage system with phase change material (PCM). *Appl Therm Eng.* 2018;144:1071–80.
  40. Sheikholeslami M. Numerical analysis of solar energy storage within a double pipe utilizing nanoparticles for expedition of melting. *Sol Energy Mater Sol Cells.* 2022;245(15):111856. <https://doi.org/10.1016/j.solmat.2022.111856>.
  41. Sheikholeslami M. Finite element method for PCM solidification in existence of CuO nanoparticles. *J Mol Liq.* 2018;265:347–55. <https://doi.org/10.1016/j.molliq.2018.05.132>.
  42. Sheikholeslami M. Efficacy of porous foam on discharging of phase change material with inclusion of hybrid nanomaterial. *J Energy Storage.* 2023;62: 106925. <https://doi.org/10.1016/j.est.2023.106925>.

**Publisher's Note** Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.