ORIGINAL PAPER

Root-soil rotation stiffness of Norway spruce (Picea abies (L.) Karst) growing on subalpine forested slopes

M. J. Jonsson \cdot A. Foetzki \cdot M. Kalberer \cdot T. Lundström · W. Ammann · V. Stöckli

Received: 15 December 2005 / Accepted: 11 April 2006 / Published online: 14 July 2006 Springer Science+Business Media B.V. 2006

Abstract Trees bend and break when exposed to external forces such as wind, rockfall, and avalanches. A common simplification when modelling the tree response to these forces is to simplify the system as a clamped beam which means that the stem deflection is related to the stem flexibility only. However, a certain part of the stem deflection originates from rotation of the root-soil plate. In this paper, we investigate this contribution to the overall stem deflection. Norway spruce (Picea abies (L.) Karst) trees were subjected to winching tests to analyse the anchorage mechanics of the tree. The tests were performed at two experimental sites with an average slope of 32 and 34° and one site with a nearly flat ground in subalpine forests near Davos, Switzerland, during the vegetation periods of 2003 and 2004. The trees were pulled downslope with a winch and the applied force, stem base rotation, and the angle of the applied force relative to the stem were recorded. After the tree had fallen over, stem diameter and branch mass were measured for every meter segment. These data were used to model the tree in the finite element software ANSYS®, which was used for calculating the rotational stem base moment as a function of stem base rotation. The root-soil rotation stiffness k_{root} was defined as the secant stiffness calculated at 0.5° root-soil plate rotation. Young's modulus of elasticity E of the stem was iteratively changed until the correct stem rotation was obtained. The best correlation between k_{root} and different tree characteristics was the squared diameter at breast height, DBH². Not incorporating the normal forces due to weight of the overhanging masses from crown and stem resulted in a maximum underestimation for k_{root} of approximately 14%. Thus, also the acting moment on the stem base will be underestimated causing the safety factor against uprooting to be overestimated.

Keywords Anchorage mechanics \cdot Finite element method \cdot Young's modulus of elasticity \cdot Tree stability \cdot Winching experiment

Nomenclature

- k_{root} root-soil rotation stiffness (kN m/rad)
- E Young's modulus of elasticity (MPa)
- DBH diameter at breast height (m)
- H_t total tree height (m)
 H_t height of applied for
- height of applied force (m)
- H_c crown length (m)
 W_t total tree mass (k
- W_t total tree mass (kg)
 W_c crown mass (kg)
- crown mass (kg)
- F applied force (kN)
- F_h horizontal force component (kN)
- F_v vertical force component (kN)

M. J. Jonsson $(\boxtimes) \cdot A$. Foetzki \cdot M. Kalberer \cdot T. Lundström · W. Ammann · V. Stöckli

WSL Swiss Federal Institute for Snow and Avalanche

Research SLF, CH-7260 Davos, Switzerland e-mail: jonsson@slf.ch

- β_F measured angle of the applied force in relation to the horizontal plane $(°)$
- ρ density of green wood (kg/m³)
- M rotational stem base moment (Nm)
- θ_0 extrapolated stem base rotation due to initial leaning of stem $(°)$
- P level of significance for the polynomial coefficients

Introduction

The root system is a crucial element for the growth and the stability of a tree. Its main functions are to provide the tree with water and nutrients and to prevent the tree from being overturned when exposed to forces resulting from wind, rockfall or avalanches. To predict the probability of uprooting for the root system, knowledge is required about the stem base moment as a function of stem base rotation, the ultimate rotational moment and the acting bending moment derived from the forces applied to the tree. The ultimate rotational moment of the root system depends on four components: (1) the mass of the root-soil plate, (2) the shear strength of the soil, (3) the resistance to failure in tension for tree roots on the windward side and (4) the resistance to bending and shear of the tree roots on the leeside (Blackwell et al. [1990\)](#page-9-0). Coutts [\(1986](#page-9-0)) investigated the relationship between these four components for Sitka spruce (Picea sitchensis (Bong.) Carr) and concluded that the major contributions to the ultimate rotational moment comes from the windward roots and the mass of the root-soil plate. To investigate the ultimate failure capacity of trees, winching experiments were carried out by a number of research teams (Fraser and Gardiner [1967](#page-9-0); Crook and Ennos [1996](#page-9-0); Moore [2000;](#page-10-0) Peltola et al. [2000\)](#page-10-0). Winching experiments were also performed on trees growing on slopes (Achim et al. [2003;](#page-9-0) Nicoll et al. [2005\)](#page-10-0), as well as on dead trees (Ammann [2005\)](#page-9-0).

Trees bend and eventually fail when exposed to external forces such as wind, rockfall, and avalanches. A common simplification when modelling the tree response to these forces is to simplify the system to a clamped beam which means that the stem deflection is related to the stem flexibility only. However, a certain part of the stem deflection originates from rotation of the root-soil plate (Neild and Wood [1999](#page-10-0)). This contribution can be quantified by means of the root-soil rotation stiffness k_{root} . The importance of taking k_{root} into account when calculating the tree response to wind is highlighted by Neild and Wood ([1999\)](#page-10-0). A more accurate prediction of the stem's bending line, the natural frequencies of the tree as well as Young's modulus of elasticity E (Yang et al. [2004](#page-10-0)) for the tree stem are obtained when including k_{root} the mechanical model of the tree. In addition to the above mentioned reasons for including k_{root} also a strong correlation with the ultimate rotational moment of the root system can be expected (Brudi and Wassenaer [2001\)](#page-9-0). Thus, knowing k_{root} , no winching experiments until failure of the root-soil system have to be conducted. However, only a few studies have been carried out to determine k_{root} (Fraser and Gardiner [1967;](#page-9-0) Neild and Wood [1999](#page-10-0)).

Norway spruce (Picea abies (L). Karst) is the most common species in European subalpine forests (Ellenberg [1996\)](#page-9-0). Of the total protection forests in Switzerland against natural hazards (rockfall and avalanches) around 56% are represented by spruce-fir forests and spruce, larch and stone-pine forests (Brassel and Brändli [1999](#page-9-0)). To accurate predict the mechanical behavior of Norway spruce trees exposed to external forces 23 Norway spruce trees growing on slopes in a subalpine forest were tested in winching experiments to quantify the root-soil rotation stiffness k_{root} for the root system and Young's modulus of elasticity E for the tree stem.

Materials and methods

Experimental sites

The winching experiments were performed at three different experimental sites (Table [1](#page-2-0)) in subalpine forests near Davos, Switzerland, during the vegetation periods (May/June–September) of 2003 and 2004. Two experimental sites are located

on slopes and one on nearly flat ground (Table 1). The vegetation type is a Norway spruce (Picea abies (L.) Karst.) forest with single European larch (Larix decidua L.). All three forest stands are moderately managed. The ground is covered by a mixture of grass (Calamagrostis villosa (Chaix) Gmel.) and dwarfshrubs, e.g., bilberry (Vaccinium myrtillus). Davos is located in the central alps in the northeast part of the canton Grisons at an altitude of 1560 m. The surroundings of Davos have an alpine topography with peaks reaching up to 3100 m. The climate is characterised by a mean annual precipitation of 1082 mm (Jan 74 mm, Aug 146 mm) of which approximately 40% is snow and an average daily temperature of 2.8 C (Jan –5.3 C , Aug 10.8 C), evaluated between 1961 and 1990 (Meteoschweiz [2004\)](#page-9-0).

The trees were exposed to moderate wind and neither rockfall and avalanches, due to the fact that all test sites were located inside the forest stand. The major wind direction in the valley of Davos is north to south with the strongest winds coming from north (Meteoschweiz [2004\)](#page-9-0). The trees on the three test sites were all mature trees with a mean diameter at breast height DBH $(±$ one standard error) 32.0±14, 40.0±15 and 26.0 ± 10 cm, and dominant height of 33.0, 35.0 and 28.0 m respectively. The stand density for respective test site was approximately 450, 320 and 580 trees per hectare. The soil at all experimental sites is a highly acid podzol (well graded gravel with silt and sand) with a good permeability and a high proportion of stones. At experimental site 3 (Table 1), preliminary tests were conducted to optimise the test set-up.

Test methods

Two different test set-ups were used for the winching experiments on five trees growing on test site 2. The first test-set up was used for winching experiments and the second test set-up was used to perform swaying experiments on the trees (M.J. Jonsson et al., submitted). Recording the data when getting the tree into release position before the swaying experiments enabled that this test set-up could also be used to evaluate the rootsoil rotation stiffness k_{root} . Thus, on these five trees two successive tests were performed.

The two test-setups used were similar to those used by e.g. Fraser and Gardiner ([1967\)](#page-9-0); Peltola et al. (2000) (2000) ; Nicoll et al. (2005) (2005) , however, adopted for our purpose. For the first test set-up, the rotations of the tree stem at 2, 5 and 20% of the total tree height H_t were recorded. The height of applied force, H_f , was 20% of H_t . For the second test set-up, the rotation of the tree stem was measured at 2, 20, 53 and 75% of H_t , and H_f was changed to 53% of H_f . The angle of the applied force β_F was measured when the pulling cable was stretched (Fig. [1](#page-3-0)) using an portable inclinometer. To record the stem rotation at 2 and 5% of H_t , an inclinometer (PMP-2.5) TZL-A-SW2 Pewatron AG, Wallisellen/Zürich, Switzerland) with a range of $\pm 2.5^{\circ}$ and a precision of ± 0.0375 ° was used. For the recording of the stem rotation at 20, 53 and 75% of H_t , inclinometers (PMP-20 TZL-A-SW2 Pewatron AG) with a range of $\pm 20^\circ$ and a precision of $\pm 0.3^\circ$ were used. The applied winching force was measured with a load cell (MTS Tensile Force Sensor, Type 85081-6100-V0000C0, 944860, Meßtechnik Schaffhausen GmbH, Neuhausen, Switzerland) with a maximum capacity of 100 kN and a precision of ± 0.2 kN. The sampling rate was 5 Hz for the first and 20 Hz for the second test set-up. To record the stem base rotation without the contribution from the stem bending deformation the sensor was mounted as low as possible on the tree stem. To avoid difficulties when attaching this sensor to the tree stem it was mounted above the buttress area and its irregularities and defined as the measured rotation at 2% of H_t . The stem section below was considered to be rigid. The trees were winched to

Fig. 1 Overview of the test set-up used for the winching experiments. H_t = total tree height, H_f = height of applied force, $F =$ applied force, F_h = horizontal force component, F_v = vertical force component, β_F = angle of the applied force

approximately 2.5° rotation at stem base, which is the full range of this sensor.

After the winching tests, some trees were used in full-scale rockfall experiments to investigate the complex interaction between a rock and a tree (T. Lundström et al., submitted). After the tree had fallen to the ground either by the rock or manually winched, crown length and total tree height were measured. For every meter segment, the stem diameter (including the bark) was measured and the mass of all branches was weighed starting from the crown base.

Analysis method

To calculate the rotational stem base moment a finite element model, FEM model, of every tree was created in the commercially available finite element code ANSYS®. To model the tree, beam elements BEAM188 (ANSYS [2002](#page-9-0)) were used which are based upon the Timoshenko beam theory which includes both shear and bending deformation. Every tree was modelled with 99 elements, respectively, 100 nodes evenly distributed over the tree height. The measured force was divided into a horizontal, F_h , and a vertical component, F_v , based upon β_F (Fig. 1).

The point of rotation of the root-soil plate was not quantified during the winching experiments. To simplify the calculation it was therefore assumed that the tree rotated around the point where the stem centreline intersects with the surface of the soil, even though it is known that the tree rotates around the leeward side of the tree trunk (Coutts [1986](#page-9-0); Nicoll et al. [2005\)](#page-10-0). The recorded stem base rotation was applied as a boundary condition at the stem base in the FEM model. For the FEM calculations the tree stem was assumed to be straight, the density of green wood and Poisson's ratio were assumed to be ρ =850 kg/m³ (unpublished data SLF) and $v=0.26$ (Kollmann and Côté 1968), respectively. The tree material was assumed to be isotropic and constant over both cross-section and height (Milne and Blackburn [1989](#page-10-0); Milne [1991\)](#page-10-0). To calculate the rotational stem base moment large deflection theory was used. This means that the extra moment from the normal forces due to overhanging tree stem and crown (branches) were taken into account. For every tree the rotational stem base moment was calculated in 100 load steps.

The rotation of the root-soil plate at a specific time can be expressed as follows:

$$
\theta_i = \theta_0 + \frac{M_i}{k_i} \tag{1}
$$

where θ_0 is the initial rotation of the root-soil plate and k_i is the secant stiffness corresponding to the stem base moment M_i . Solving for k_i gives the following relationship:

$$
k_i = \frac{M_i}{\theta_i - \theta_0} \tag{2}
$$

To estimate θ_0 a linear elastic interval was introduced between 0 and 0.1° stem base rotation θ_i , which is lower than the elastic interval of 0.25° suggested by (Brudi and Wassenaer ([2001\)](#page-9-0). Using the least square method to solve the equation system, θ_0 and the initial stiffness for this assumed linear elastic interval could be calculated. To estimate k_i the following methodology was applied:

- the recorded rotations and applied force data were averaged over one second to smooth the data.
- the Young's modulus of elasticity E for the stem was iteratively changed until measured and calculated rotation for all the inclinometers differed less than 5%.
- the rotational stem base moment M_i was plotted against the stem base rotation θ_i , and the least square method was used to calculate θ_0 (Fig. 2).
- the secant stiffness was calculated according to Eq. 2 for every measured value of θ_i .

To compare the stiffness between all trees the calculated secant stiffness k_i for 0.5° stem base rotation was used. This value was selected because all trees were winched to at least 0.5° stem

Fig. 2 Overview of the rotational stem base moment versus rotation at stem base θ , θ_0 extrapolated stem base rotation due to initial leaning of stem

base rotation which then allowed a comparison between all the trees. The calculated secant stiffness for 0.5° rotation of the root-soil plate is referred to as the root-soil rotation stiffness and noted as k_{root} .

The data were investigated with the commercial software S-plus[®] (Insightful Corporation, Seattle, Washington, USA) using regression analysis. The regressions were forced to intercept with the origin as this is physically meaningful. When DBH, H_t or stem masses etc. are zero, k_{root} and E must be zero as well. The regression analysis was checked regarding the level of significance for polynomial terms using the F-test, and the sum of squared errors, R^2 . A relation between evaluated results were considered useful if $R^2 > 0.5$, and the polynomial coefficients, p_i , meaningful if their level of significance $P < 0.05$.

To investigate the sensitivity of k_{root} to the input parameters, three trees from experimental site 2 were selected (Table 2). For these trees the crown mass, Young's modulus of elasticity and density were all changed with $\pm 25\%$ and the influence on k_{root} was analysed.

Results

By iteratively changing Young's modulus of elasticity E for the tree stem until the measured and calculated stem rotation corresponded, it was possible to estimate the elasticity for the tree stem (Fig. [3](#page-5-0)).

For all trees the secant stiffness decreased as the stem base rotation increased (Fig. [4](#page-5-0)).

When performing two successional tests, the calculated secant stiffness was always lower for the second test (Table [3](#page-6-0)). This is not only valid for a specific point, but for the whole recorded

Table 2 Geometric properties of the trees growing in experimental site 2, used in the sensitivity analysis of the root-soil rotation stiffness k_{root} , H_t = total tree height, H_c = crown length, W_t = total tree mass and W_c = crown mass

Tree no.	$H_{\rm t}$ (m)	H_c (m)	W_c (kg)	W_t (kg)
\mathcal{L}	32.9	6.1	505	3031
$\overline{4}$	33.5	9.25	283	3408
	27.9	6.2	284	1698

Fig. 3 Calculated stem rotation at 20% of total tree height H_t for tree 1 experimental site 2. The time indicate the total time for the winching experiment

range (Fig. 5). The decrease in k_{root} calculated at 0.5° rotation of the root-soil plate between the first and second test was on average 30.9% $(n = 5)$.

The measured rotation of the root-soil plate sometimes indicated a residual rotation at the tree base after the force was released. Due to this finding and the difference in secant stiffness between two successional test for the same tree, only the first performed test was included in the future statistical analysis. This means that tests with H_f at 20% of H_t for tree No. 1, 2, 4, 5 and 3.b from experimental site 2 were excluded from the statistical analysis (Table [3\)](#page-6-0).

Fig. 4 Calculated secant stiffness as a function of stem base rotation θ for tree no. 3, 4 and 5 at experimental site 1. Tree 4 has a smaller diameter at breast height DBH but a larger stiffness compared to tree 5

Fig. 5 Secant stiffness as a function of stem base rotation θ for two trees tested twice, the trees are from experimental site 2. The secant stiffness is lower for both trees during the second experiment

No statistical investigation was made regarding the difference in stiffness due to slope exposition, because of the low number of tests on the sites 1 and 3. For the remaining 18 tests, the model $k_{\text{root}} = p_1$. DBH² was best fitted to the data. Including all tests gave a significant value of p_1 . One outlier was observed and identified as tree 3, experimental site 3. The E for this tree was almost three times higher than the average value for all trees. Although we found no visual damages on this tree e.g. rockfall scars or rot we excluded it from the statistical analysis due to possibilities of unobserved damage. For k_{root} this resulted in p_1 =28427 and $P < 0.001$ with R^2 =0.64 (Fig. [6\)](#page-6-0).

No correlation for E with tree characteristics such as DBH and H_t were found when including all trees in the statistical analysis. Therefore, only the mean value, $\overline{E} = 8289$ MPa, and the standard deviation, σ =3602 MPa were calculated. Excluding tree 3 at experimental site 3 with the same motivation as above and calculating mean and standard deviation resulted in $\overline{E} = 7634 \text{ MPa}$, σ =1803 MPa.

To investigate the sensitivity of k_{root} to the normal forces due to overhanging stem and crown mass, three trees were selected for further investigations. Excluding the crown mass the maximum underestimation of k_{root} were 8.1% (Table [4\)](#page-7-0). Excluding the stem weight by setting its density to 1 kg/m³ and the crown mass to zero resulted in a Table 3 Root-soil rotation stiffness k_{root} and Young's modulus of elasticity E for all the trees, DBH = diameter at breast height $H_t =$ total tree height H_f = height of applied force. For tree 3 at experimental site 2, two tests were performed with the same H_f , test 3.a is included in the analysis

underestimation of k_{root} by 19.6, 9.7 and 13.5%, respectively (Table [4\)](#page-7-0). Comparing these results with the results obtained when only the crown mass is removed indicates that the contribution of the overhanging stem is about 11.6, 7.5 and 8.0%, respectively. A change of $\pm 25\%$ in E and the stem density resulted in a maximum increase of

Fig. 6 Relationship between root-soil rotation stiffness k_{root} and diameter at breast hight squared DBH² for the 17 tests included in the regression analysis, $k_{\text{root}} = p_1 \cdot DBH^2$, $p_1 = 28427$ and $R^2 = 0.64$. Upper and lower dotted lines shows limits for the 95% confidence interval

9.7% and a maximum decrease of 4.8% for k_{root} $(Table 4)$ $(Table 4)$.

Discussion

Analysis method and test set-up

To accurate predict the mechanical behavior of Norway spruce trees growing on slopes in a subalpine forest winching experiments were conducted to quantify the behavior of the rootsoil rotation stiffness and Young's modulus of elasticity E for the tree stem. The influence of the normal forces due to the overhanging crown mass, stem and the vertical force component can easily be included when using a commercial finite element software. These are factors that should be included in the analysis when evaluating tree winching experiments. Neglecting this contribution will result in an underestimation of E for the stem and a less precise prediction of the stem bending axis (Neild and Wood [1999;](#page-10-0) Peltola et al. [2000\)](#page-10-0). We also showed that neglecting the normal forces caused by the overhanging stem and tree crown resulted in a maximum underestimation of the root-soil rotation stiffness k_{root} with

Table 4 root-soil k_{root} when Young's n elasticity green wo crown ma

approximately 14% (Table 4). This is in accordance with the values proposed by Peltola et al. [\(2000](#page-10-0)), who calculated the rotational stem base moment to be underestimated by 5–20%, depending upon tree size. Thus, the acting moment on the stem base will be underestimated causing the safety factor against uprooting to be overestimated.

Root-soil rotation stiffness k_{root}

Many mechanical models have been developed to analyze wind interaction with trees (Saunderson et al. [1999](#page-10-0); Peltola et al. [1999](#page-10-0); Gardiner et al. [2000\)](#page-9-0). However, a common assumption is to model the root-soil system with no flexibility, even though it is known that a better prediction of the bending line (Neild and Wood [1999](#page-10-0); Yang et al. [2004\)](#page-10-0), and thus the acting moment of the stem base is obtained. The reason for not including the flexibility is believed to be mostly due to lack of quantitative information for the moment versus stem base rotation relation. However, including the flexibility does not only improve the prediction of the tree's behavior with wind interaction. All transient processes such as

rock impact on trees and avalanche interaction with trees can be much better understood.

The evaluation routine proposed here defines k_{root} as a function of stem base rotation. When defining k_{root} as not constant, the question arises as to which value should be used. This can be answered with measurements of the stem base rotation during specific wind actions. We suggest using values corresponding to the most frequent rotation at the stem base during a certain wind speed. It has been shown that the ultimate rotational moment for the stem base changes only slightly in different directions to the slope (Achim et al. [2003\)](#page-9-0). From these results we suggest the use of the same value of k_{root} for all the directions until quantitative data exist about the behaviour of the root-soil system in all four directions of the slope.

It was also observed that the secant stiffness decreased with increasing rotation. This decrease was observed from the very beginning of the re-sults (Fig. [4](#page-5-0)). In case of an elastic interval of 0.25° suggested by Brudi and Wassenaer [\(2001](#page-9-0)) no decrease in k_{root} would be observed and a constant value would be found. Therefore, the obtained results indicate that the elastic interval is very small, and might not even exist at all. Five tests

were carried out to investigate whether there is a difference in k_{root} when performing two successional tests. A difference between these tests was always observed (Table [3,](#page-6-0) Fig. [5\)](#page-5-0). This might originate from the fact that the plastic part of the deformation curve in the root-soil plate is reached. Even at a small inclination k_{root} decreases when two successive tests are done. This could indicate that using the method suggested by Brudi and Wassenaer ([2001\)](#page-9-0) to investigate the tree stability the tested trees are not nondestructive tested and the residual ultimate rotational moment for the root-system might be overestimated. However, the tests were conducted during the same day and it must be further investigated to see whether the same results can be expected after more days and weeks, as this would give information about the healing process of the root-soil system.

Analysing the stem base rotation shows a residual rotation of the root-soil plate when the force is released. This supports the idea that the deformation of the root-soil plate enters the plastic range. The reason for this deformation might be deformation (damages) in the soil which leads to a redistribution of the soil material, or damage to the fine roots or a combinations of both. Coutts [\(1983](#page-9-0)) performed winching experiments on Sitka spruce (Picea sitchensis (Bong.) Carr) trees (34 year old co-dominant trees with a mean height of 20 m and mean DBH of 21 cm) and recorded the breakage of roots/soil using buried microphones. On the windward side of the root-soil plate an upward movement was observed and sequential breakage of roots/soil were observed at approximately $0.5-1^\circ$ rotation at stem base. Another possible method to reveal which of these processes that are responsible for the residual rotation would be to investigate the changes in sapflow pattern during winching experiments on trees. Such investigations were performed on Maritime Pine (Pinus pinaster Ait) and oak (Quercus petraea) trees winched up to 10° inclination (measured at the cable attachment point 3.6 m. No information is given about the stem base rotation.) (Stokes et al. [2000\)](#page-10-0). During the experiments a decrease in sapflow was observed only in the oak tree. The suggested explanation was stretching and compression of the longitudinal wood cells and thereby a temporarily redistribution of the sapflow. However, the tested trees were small DBH=13.1 cm and it is known that smaller trees are much more elastic and the effect of root/soil breakage might not have been observed. Thus, to reveal if the major process is breakage of the roots or the soil it is suggested that sapflow measurements are performed on larger trees in combination with carefully monitoring of the of the stem base rotation, or monitoring of midterm reaction of trees such as growth performance.

Because of annual variations in the soil water content, soil shear strength and cohesion forces between soil and roots, a variation of the ultimate rotational moment for the root system can be observed (Crook and Ennos [1996\)](#page-9-0). The ultimate rotational moment and k_{root} are closely connected which indicate that k_{root} also changes with annual variations. Not only the soil properties effect k_{root} . The size of the root-soil plate, root architecture and the root-cross sectional area effect the ultimate rotational moment. These properties then effect the mass of the root-soil plate as well as the point of rotation for the a tree, factors that both increase the ultimate rotational moment at the stem base as well as k_{root} (Coutts [1986;](#page-9-0) Blackwell et al. [1990](#page-9-0); Bolkenius [2001](#page-9-0)).

Modulus of elasticity of the stem E

A common method used to obtain Young's modulus of elasticity E for the tree stem in bending is to iteratively chang its value until the measured and calculated stem bending axis agree (Milne and Blackburn [1989](#page-10-0); Milne [1991\)](#page-10-0). We have in this paper shown that it is also possible to estimate E when iteratively change its value until measured and calculated stem rotations correspond (Fig. [3](#page-5-0)). Comparing the obtained results with those from Peltola et al. [\(2000](#page-10-0)) (boreal areas) and Bruchert et al. [\(2000](#page-9-0)) (montane areas) shows that the E are in the same order of magnitude.

The calculated value of E for tree 3 at experimental site 3 is almost three times higher than the calculated average value for all trees. Also the k_{root} is much higher for this tree (Table [3\)](#page-6-0). The experimental site 3 was mainly used for tuning the test set-up. The high value of both E and k_{root} could indicate a problem with the test set-up. Studying the root architecture of this tree a large root-buttress was observed. Furthermore, this tree was growing on a small knoll exposed to wind. Both factors that might contribute to an increased stability. However, the root system showed an irregular root distribution with only two big lateral roots and the root-soil plate was smaller than for other trees with the same DBH,

factors that lead to a lower stability.

Conclusions

- To iteratively change Young's modulus of elasticity E for the stem until measured and calculated rotation for all the inclinometers correspond can be used to estimate the modulus of elasticity.
- Using the full power of a finite element code makes it possible to include the vertical forces due to the overhanging mass from stem and crown. Neglecting these two factors resulted in an underestimation of k_{root} by up to 14%.
- To use this data for predicting the critical wind speeds for a tree to overturn, knowledge is required about the root-soil rotation stiffness k_{root} in all four directions of the slope as well as the rotation at stem base during certain wind speeds. With the data now available the exposure of a tree to downslope forces such as rockfall and avalanches can be more accurately modelled. However, further research must be done to quantify the behaviour of the root-soil system in all four directions to the slope.
- The elastic interval of 0.25° rotation of the root-soil plate could not be verified, in this investigation no elastic interval was found for the rotation of the root-soil plate.
- The measured rotation of the root-soil plate sometimes indicated a residual rotation at the tree base after the force was released. Where this remaining deformation originates from must be further investigated.

Acknowledgements This study was supported by the Board of the Swiss Federal Institutes of Technology. We thank the landowners of the experimental sites for allowing us to perform the experiments, ''Forstwerkhof Davos'' for providing useful help during the fieldwork, Holger Simon for conducting the field experiments, Prof. Dr.

Alessandro Dazio (Institut für Baustatik und Konstruktion ETH-Zurich) and the anonymous reviewers of this paper.

References

- Achim A, Nicoll B, Mochan S, Gardiner B (2003) Wind stability of trees on slopes. In: Ruck B, Kottmeier C, Mattheck C, Quine C, Wilhelm G (eds) International conference wind effects on trees. Laboratory for Building- and Environmental Aerodynamics, Inst. for Hydromechanics, University of Karlsruhe, Germany, pp 231–237
- Ammann M (2005) Abgestorbene Bäume: Mechanische Eigenschaften und Schutzwirkung gegen Naturgefahren. Holzforschung Schweiz 1:4–5
- ANSYS (2002) ANSYS, Inc. theory reference, verison 7.0, Canonsburg, USA
- Blackwell PG, Rennolls K, Coutts MP (1990) A root anchorage model for shallowly rooted Sitka Spruce. Forestry 63:73–91
- Bolkenius D (2001) Zur Wurtzelausbildung von Fichte (Picea abies L. [Karst] und weißbanne (Abies alba Mill.) in gleich- und ungleichhaltrigen Bestände. Berichte Freiburger Forstliche Forschung Heft, p 35
- Brassel P, Brändli UB (1999) Schweizerisches Landesforstinventar. Ergebnisse der Zweitaufnahme 1993–1995. Paul Haupt, Bern Stuttgart Wien, pp 442
- Brüchert F, Becker G, Speck T (2000) The mechanics of Norway spruce [Picea abies (L.) Karst]: mechanical properties of standing trees from different thinning regimes. Forest Ecol Manag 135:45–62
- Brudi E, Wassenaer PV (2001) Trees and statics: nondestructive failure analysis. In: Thomas ES, Kim DK (eds) Tree structure and mechanics conference proceedings: how trees stand up and fall down. International Soc. of Arboriculture, pp 53–69
- Coutts MP (1983) Root architecture and tree stability. Plant Soil 71:171–188
- Coutts MP (1986) Components of tree stability in Sitka Spruce on peaty gley soil. Forestry 59:173–197
- Crook MJ, Ennos AR (1996) The anchorage mechanics of deep rooted larch, Larix europea x L. japonica. J Exp Bot 47:1509–1517
- Ellenberg H (1996) Vegetation Mitteleuropas mit den Alpen in ökologischer, dynamischer und historischer Sicht. Ulmer, Stuttgart, pp 1093
- Fraser AI, Gardiner JBH (1967) Rooting and stability in Sitka Spruce. For Commission Bull 40:1–28
- Gardiner BA, Peltola H, Kellomäki S (2000) Comparison of two models for predicting the critical wind speeds required to damage coniferous trees. Ecol Model 129:1–23
- Kollman FPP, Côté WA (1968) Principles of wood science and technology. I, Solid wood. Springer-Verlag, pp 502
- Meteoschweiz (2004) Messstation Davos. http://www.meteoschweiz.ch/- de/Klima/Klimapublikationen/Index-Klimapublikationen.shtml.
- Milne R (1991) Dynamics of swaying of Picea sitchensis. Tree Physiol 9:383–399
- Milne R, Blackburn P (1989) The elasticity and vertical distribution of stress within stems of Picea sitchensis. Tree Physiol 5:195–205
- Moore JR (2000) Differences in maximum resistive bending moments of Pinus radiata trees grown on a range of soil types. Forest Ecol Manag 135:63–71
- Neild SA, Wood CJ (1999) Estimating stem and rootanchorage flexibility in trees. Tree Physiol 19:141–151
- Nicoll BC, Achim A, Mochen S, Gardiner BA (2005) Does steep terrain influence tree stability? A field investigation. Can J For Res 35:2360–2367
- Peltola H, Kellomäki S, Väisänen H, PIV (1999) A mechanistic model for assessing the risk of wind and snow damage to single trees and stands of Scots pine, Norway Spruce and Birch. Can J For Res 29:647–661
- Peltola H, Kellomäki S, Hassinen A, Granander M (2000) Mechanical stability of Scots pine, Norway spruce and Birch: an analysis of tree-pulling experiments in Finland. Forest Ecol Manag 135:143–153
- Saunderson SET, England AH, Baker CJ (1999) A dynamic model of the behaviour of Sitka Spruce in high winds. J Theor Biol 200:249–259
- Stokes A, Berthier S, Nadhezdhina NJC, Loustau D (2000) Sap flow in trees is influenced by stem movement. In: Spatz HZ, Speck T (eds) Plant biomechanics 2000: proceedings of the 3rd plant biomechanics conference freiburg-badenweiler, 27 August–2 September, 2000. Stuttgart, Thieme, pp 272–277
- Yang YB, Yang YT, Su HH (2004) Behavior of the tree branches, trunk, and root anchorage by nonlinear finite element analysis. Adv Struct Eng 7:1–14