



Correction to: Influence of Extrusion Speed on the Microstructure Evolution, Interface Bonding and Mechanical Response of Mg MB26/Al 7075 Composite Rod

Yu Chen¹ · Rui Zhang¹ · Tao Zhou¹ · Li Hu¹ · Jian Tu¹ · Lai-Xin Shi¹ · Yan Zhi¹ · Li-Wei Lu² · Qiang Chen^{3,4} · Ben-Hong Liao¹ · Lei Liu¹ · Wen-Jun Ge¹ · Jing Xiao¹ · Ming-Bo Yang¹

© The Chinese Society for Metals (CSM) and Springer-Verlag GmbH Germany, part of Springer Nature 2024

Correction to:

**Acta Metallurgica Sinica (English Letters) (2019)
32:253–262**
<https://doi.org/10.1007/s40195-018-0838-x>

Error in Table

In the original publication [1], there was an error in the contents of Mn element and Cr element in Table 1. The *corrected* Table 1 appears below.

Text Correction

In the original publication [1], there was an error in the sentence of “The as-extrusion rods were kept in muffle furnace

at 400 °C for 2 h to complete solid solution of Al 7075; the billets and die were preheated at 430 °C and then immediately extruded at 320 °C with an extrusion ratio 25:1 and an extrusion speed of 0.3, 0.7, 1.2 and 2.1 mm/s, respectively.”

A correction has been made to the “2.1 Fabrication of Mg/Al Composite Rod”, “Paragraph 1”:

“The billets were preheated at 400 °C for 2 h and then immediately extruded at 320 °C with an extrusion ratio 25:1 and an extrusion speed of 0.3, 0.7, 1.2 and 2.1 mm/s, respectively.”

The authors would like to apologize for any inconvenience caused.

The original article can be found online at <https://doi.org/10.1007/s40195-018-0838-x>.

✉ Tao Zhou
zt19811118@cqut.edu.cn

✉ Jian Tu
tujian@cqut.edu.cn

✉ Qiang Chen
2009chenqiang@163.com

¹ College of Material Science and Engineering, Chongqing University of Technology, Chongqing 400054, China

² Institute of Light Metal Structural Materials, Hunan University of Science and Technology, Xiangtan 411201, China

³ Southwest Technology and Engineering Research Institute, Chongqing 400039, China

⁴ Precision Forming Integrated Manufacturing Technology of Collaborative Innovation Center, Chongqing 400039, China

Table 1 Chemical composition of the base metal in the test (mass fraction, %)

Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Al	Zr	RE
7075	≤0.4	≤0.5	1.2–2.0	≤0.3	2.1–2.9	0.18–0.28	5.1–6.1	≤0.2	Bal.	–	–
MB26					Bal.		5.9			0.6	1.0

Reference

1. Y. Chen, R. Zhang, T. Zhou, L. Hu, J. Tu, L.X. Shi, Y. Zhi, L.W. Lu, Q. Chen, B.H. Liao, L. Liu, Influence of extrusion speed on

the microstructure evolution, interface bonding and mechanical response of Mg MB26/Al 7075 composite rod. *Acta Metall. Sin. (Engl. Lett.)* **32**, 253–262 (2019)